

# SENSO

#### SELF-ADHESIVE VINYL PLANKS & TILES

# BENEFITS

REAL-WOOD LOOK AND EXCLUSIVE FINISHES FOR PERFECT STYLE

QUICK INSTALLATION

**IDEAL FOR RENOVATIONS** 

SUITABLE FOR HIGH-HUMIDITY ROOMS

EASY TO CLEAN, ECONOMICAL AND ECO-FRIENDLY

Textured, matt finish surface Wide selection of exclusive edges

- No gluing: self-adhesive
- No tools needed: can be trimmed with a utility knife

2mm thick: doors don't have to be shortened

Watertight and slip-resistant

Clean with soapy water or neutral detergent



# TECHNICAL CHARACTERISTICS

		Planks	Tiles	
THICKNESS	mm	2	2	
WEAR LAYER THICKNESS	mm	0,2	0,2	
WEIGHT	g/m²	3920	3425	
DIMENSIONS	cm	91,4 x 15,2 / 91,4 x 18,4	40,6 x 40,6 / 45,7 x 45,7 / 30,5 x 60,9	
AREA PER BOX	m²	2,2 / 2,69	1,3 / 2,29 / 2,22	
TILES & PLANKS PER BOX	Planks / Tiles	16	8 / 11 / 12	
SURFACE		Varnished	Varnished	
EUROPEAN CLASSIFICATION	Class	22	22	
FIRE RATING	Class	BflS1	BflS1	
SOUND INSULATION	dB	3	3	
WATER RESISTANCE		Compatible with wet rooms		
RESIDENTIAL USE GUARANTEE*	Years	10	10	

<sup>\*</sup> For more details on guarantee, see www.gerflor.com







#### SELF-ADHESIVE VINYL PLANKS & TILES

## **INSTALLATION TIPS**

- TOOLS REQUIRED: ruler, utility knife, tape measure
- Check that all planks have the same batch number
- Store the planks in the room, flat and face up, for 24 hours prior to installation

	IRT TO	

INSTALLATION
POSSIBILITIES ACCORDING

TO SUBFLOOR\*

**HEATED FLOORING** 

ESTIMATED INSTALLATION TIME

**EXPOSURE** 

Flatness tolerance Step tolerance

On carpet

On seamless tile (granite-type)

On tile (with joints)

On laminate

On concrete

On PVC (compact)

On solid or engineered wood floor with ventilated underside

ventitated underside

> 28°C

< 28°C

Reversible

Anhydrite coating

For 12m<sup>2</sup> (125 sq.ft.)

For  $> 12m^2$  (125 sq.ft.)

Veranda

Skylight

\* For more details on installation, see instructions on www.gerflor.com

Νo

No Remove subfloor

Yes

No Resurfacing required

No Remove subfloor

Yes, if original surface is smooth

No Remove subfloor

Under certain conditions

(see warning)

Νo

Yes

Nο

Under certain conditions (see warning)

2 hours

15m<sup>2</sup>/hour (160 sq.ft./hour)

Νo

Νo



TECHNICAL TIP:
Apply Gerflor Primer to your floor to improve product adherence.



### ENVIRONMENT



#### **HEALTH**

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer

#### **ENVIRONMENT**

- 100% recyclable
- Soapy water cleaning