


DESCRIPTION			
Total thickness	-	mm	1.50
Thickness of transparent decorative layer	-	mm	0.10
Thickness of resistance layer	-	mm	1.4
Weight	-	g/sqm	2550
Width	EN 233	cm	200
Length	EN 233	lm	21
CLASSIFICATION			
Norm / Product specification	-	-	EN 259-1
Fire classification	EN 13 501-1	class	B- s2,d0
PERFORMANCES			
Curving after exposure to heat	ISO 23999 - EN 434		≤ 2 mm
Colour fastness	EN ISO 20 105 - B02	degree	≥ 6
Surface treatment	-	-	PROTECSOL
Chemical resistance (1)	EN ISO 26987	-	OK
Cleanability	EN 233		Washable and brushable
Emission of particles	ISO 14644-1	class	Class 3
Anti-bacterial activity (E. coli -S. aureus -MRSA (2))	ISO 22196	-	> 99 % inhibits growth
Resistance to impacts	EN 259-2	-	No visible bursting or cracking
Scratch resistance	NF EN 14565 annex A		No visible deterioration
Determination of flexibility	EN ISO 24344		No damage, no cracking
Resistance of welded joints	EN 684	N/50mm	≥ 250
ENVIRONMENT / AIR QUALITY			
TVOC after 28 days	ISO 16516	µg/ m3	<10
Recyclability	-	-	100%
Recycled content	-	-	Up to 30%
	EN 15 102	-	OK

(1) Regarding the resistance to chemicals, please download the corresponding leaflet from our website

(2) The implementation of an effective cleaning regime is the most important defence against infection