

MIPOLAM AFFINITY & MIPOLAM ACCORD

Homogeneous
Sheet Flooring



Div. 9



MIPOLAM AFFINITY & MIPOLAM ACCORD

gerflorusa.com



Gerflor[®]

Gerflor[®]
theflooringgroup

MIPOLAM AFFINITY & MIPOLAM ACCORD

4447 Light Emerald | AFFINITY
WR: 2885




0447 Grunsee | ACCORD
WR: 2885

MIPOLAM AFFINITY & MIPOLAM ACCORD

Specifications have been built on Gerflor for 80 years. Mipolam, the original homogeneous sheet flooring, continues to be the most durable on the market, with leading innovations such as the chemical stain resistant surface treatment, Evercare™, and bio-based formulas.

New: Mipolam Affinity features a non-directional design available in 28 tone-on-tone colors that coordinate with Mipolam Accord.

NEW! **MIPOLAM AFFINITY:** Tone-on-tone, non-directional design




MIPOLAM ACCORD: Semi-directional, marbled design

ORIGINAL DESIGN

Mipolam Affinity and Mipolam Accord are 0.08" (2 mm) thick monolayer homogeneous vinyl flooring, and are available in 6'6" wide sheets with Evercare™ surface treatment.

PROVEN PERFORMANCE

- Durable, with fewer fillers than the industry standard to provide superior resistance to heavy traffic abrasion, from permanent equipment to wheeled traffic and hospital beds. Will withstand up to 2,000 lb/in² static load limit (ASTM F970), for a 20+ year life expectancy.
- No wax maintenance protocol with Evercare™ surface treatment.
- Naturally bacteriostatic to help stop the spread of common hospital acquired infections, such as MRSA and E. Coli.
- Matte, non-glaring surface recommended in healthcare applications.
- Lightweight, flexible homogeneous flooring makes for easy installation, coving, skirting, and welding.
- True colors that never fade and keep their original tone.



MIPOLAM AFFINITY & MIPOLAM ACCORD



LCA

- Third party certified product-specific Type III EPD
- Made in an ISO 14001 and 9001 certified manufacturing plant
- Extremely durable with an over 20 year life expectancy



INDOOR AIR QUALITY

Creating a healthy environment for patient and staff well being and recovery

- Extremely low VOC emissions—less than 10 µg/m3, 100 times better than industry requirements
- FloorScore® certified
- Allergen free
- No wax finish | No need for additional chemicals



RAW MATERIALS

- 100% REACH compliant
- FREE of formaldehyde
- NO heavy metals and NO solvents



WELLNESS

- Naturally bacteriostatic to limit the spread of infections. ISO 22196 certified at >99%
- Evercare™ surface treatment — resulting in durable, best in class stain resistance, no need for a floor finish or harsh chemicals




RECYCLED CONTENT

- 25% pre-consumer recycled content
- Recycled content is 100% REACH compliant




4457 Olivine | AFFINITY
WR: 2884



0457 Como | ACCORD
WR: 2884

4405 Sand Opal | AFFINITY
WR: 2862



0305 Light Sand | ACCORD
WR: 2862

4403 Natural Shade | AFFINITY
WR: 0498



0303 Manitoba | ACCORD
WR: 0498

4425 Amber | AFFINITY
WR: 2634



0425 Cork | ACCORD
WR: 2634

4432 Citrine | AFFINITY
WR: 0110



0332 Dore | ACCORD
WR: 0110

4424 Smoked Opal | AFFINITY
WR: 2614




0324 Sand | ACCORD
WR: 2614

4448 Ruby | AFFINITY
WR: 2879





0448 Bandak | ACCORD
WR: 2879

4455 Orange Sunlight | AFFINITY
WR: 2913



0315 Orange River | ACCORD
WR: 2913

4437 Cashmere Rose | AFFINITY
WR: 0007



0437 Flamingo Resort | ACCORD
WR: 0007

GERFLOR: ACTIONS SPEAK LOUDER THAN WORDS





MIPOLAM AFFINITY & MIPOLAM ACCORD




MIPOLAM

4445 Mocca | AFFINITY
WR: 2573



0445 Otto | ACCORD
WR: 2573

4460 Black Stone | AFFINITY
WR: 2320



0360 Balaton | ACCORD
WR: 2320

4459 Grey Storm | AFFINITY
WR: 2272



0459 Mississippi | ACCORD
WR: 2272

4430 Pearl Grey | AFFINITY
WR: 0075




0330 Kruger | ACCORD
WR: 0075

4417 Aquamarine | AFFINITY
WR: 2375



0417 Constance | ACCORD
WR: 2375

4446 Blue Ocean | AFFINITY
WR: 0691



0346 Roxen | ACCORD
WR: 0691

4443 Lime Taupe | AFFINITY
WR: 2883



0443 Krumme | ACCORD
WR: 2883

4463 Greige | AFFINITY
WR: 2762




0463 Bourget | ACCORD
WR: 2762

4429 Grey Opal | AFFINITY
WR: 0069



0319 Toba | ACCORD
WR: 0069

4410 Violet Grey | AFFINITY
WR: 2633




0310 Huron | ACCORD
WR: 2633

4496 Light Sapphire | AFFINITY
WR: 2644



0306 Inari | ACCORD
WR: 2644

4416 Sapphire | AFFINITY
WR: 0500



0316 Malaren | ACCORD
WR: 0500

4401 Quartz | AFFINITY
WR: 2882



0301 Louise | ACCORD
WR: 2882

4441 Light Greige | AFFINITY
WR: 0645



0441 Loch Ness | ACCORD
WR: 0645

4408 Crystal Ice | AFFINITY
WR: 0196




0321 Salt | ACCORD
WR: 0196

4409 Matte Grey | AFFINITY
WR: 2415




0312 Powell | ACCORD
WR: 2415

4450 Stormy Weather | AFFINITY
WR: 2880



0450 Thames | ACCORD
WR: 2880


4420 Silver Grey | AFFINITY
WR: 2881



0320 Ontario | ACCORD
WR: 2881



NO WAX FOR LIFE.
CHEMICAL AND STAIN
RESISTANT SURFACE
TREATMENT.



GERFLOR USA
877.437.3567
info@gerflorusa.com



GERFLOR CANADA
438.333.0752
gerflorcanada@gerflor.com

gerflorusa.com
gerflorcanada.com

DESCRIPTION	STANDARDS	REQUIREMENTS	MIPOLAM ACCORD	MIPOLAM AFFINITY
PRODUCT DESCRIPTION				
Reference Specification	ASTM F1913		Meets Requirements	
Construction			Homogeneous sheet vinyl flooring	
Patterns			Semi-directional marbleized design	Tone-on-tone non-directional design
Colors			28	28
Surface Treatment / Maintenance	—		Evercare™ / No wax for life	
Gauge Total Thickness	ASTM F386	≥ 0.075 in	0.08" (2.0 mm)	
Wearlayer Thickness	ASTM F410		0.08" (2.0 mm)	
Roll Width	—		6' - 6" (2 m)	
Roll Length	—		66' (20 m)	
Coverage / Roll	—		430.56 sqf (40 sqm)	
Weight	—		0.58lbs/sqf (2850 g/sqm)	
PERFORMANCE				
Static Load (250 psi)	ASTM F970	≤ 0.005 in	-0.002 (Meets Requirements)	
Maximum Static Load Limit	ASTM F970		Up to 2000 lbs	
Abrasion	ASTM F510		≤ -3 mm	
Indentation – Residual	ASTM F1914	≤ 0.007 in	-0.005 inch	
Flexibility	ASTM F137	> 1 1/2 in	Exceeds	
Chemical & Stain Resistance	ASTM F925		Excellent; Test results available upon request	
Resistance to Heat	ASTM F1514	ΔE ≤ 8	Meets Requirements	
Resistance to Light	ASTM F1515	ΔE ≤ 8	Meets Requirements	
Coefficient of Friction	ASTM D2047		0.56 (Meets Requirements)	
Coefficient of Friction	ASTM C1028		0.83 (Meets Requirements)	
Dimensional Stability	—		Excellent	
Impact Insulation Class (IIC)	ASTM E989 (ASTM E 492)		42	
Fire Rating	ASTM E648	Class I	Class 1	
	CAN/ULC S102.2		Tested in accordance	
ENVIRONMENT HEALTH & SAFETY				
Indoor Air Quality / Low Emitting Materials	EQc2 Leed v4		FloorScore®	
TVOC after 28 days	ISO 16000-6	—	< 10 µg/ m3	
Naturally Bacteriostatic - Limits MRSA, E Coli, and S Aureus infections spread*	ISO 22196		> 99%	
Allergen Free			OK	
Restriction Use of Harmful Chemicals	MRc4 Leed v4		Complies with REACH	
Environmental Product Declarations (EPD)	MRc2 Leed v4		Product-Specific Type III	
Plant Certifications			ISO 14001, ISO 9001, OHSAS 18001	
Production Waste	MRc3 Leed v4		100% Manufacturing Waste Recycled	
Recycled Content	MRc3 Leed v4		25%	
End of Life			100% Recyclable	
WARRANTY:	10-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on www.gerflorusa.com.			

* The best defense against the spread of infections is the implementation of an effective cleaning method



Follow us on social media!

Gerflor
theflooringgroup