














POPIS			
Celková tloušťka	EN ISO 24346	mm	3.2
Rubová vrstva	-	-	Jute fabric
Hmotnost	EN ISO 23997	g/sqm	3800
Šířka role	EN ISO 24341	cm	200
Délka role	EN ISO 24341	m	App. 28
Složení materiálu	98% natural materials (bio-based and mineral) : linseed oil, wood flour, resins, cork, minerals, jute fabric, among which 76% are rapidly renewable. 100 % recyclable, contains up to 40 % recycled		
KLASIFIKACE			
Specifikace produktu	-	-	EN 14904 / DIN 18032-2
Evropská klasifikace	EN ISO 10874	class	23 / 34 / 43
Hořlavost	EN 13501-1	class	Cfl-s1*
Dynamický součinitel tření	EN 13893	-	0.4μ -0.6μ Fulfilled
Tření	EN 14904	-	80-110 Fulfilled
Kročejevý útlum zvuku	EN ISO 717-2	dB	6 dB
VLASTNOSTI			
Zbytkový otlak	EN ISO 24343-1	mm	≤ 0.15
Stálobarevnost	EN ISO 105 - B02	degree	≥6
Odraz světla	VDE 0100	-	p≥0.20 Fulfilled
Vznik. el. náboje	EN 1815	kV	app. 2.0
Test kolečkovou židlí (Typ W)	ISO 4918	-	OK
Tepelný odpor	EN 12667	Sqm,K/W	0.018
Tepelná vodivost	EN ISO 10456	W/(m.K)	0.17
Odolnost vůči chemikáliím	EN ISO 26987	class	OK
CIRCULAR ECONOMY			
Certification	Cradle to Cradle	-	Silver
CERTIFIKACE			
       			
CE MARKING			
	EN 14904 : 2006	-	   

* Glued according to certificate.

DOP numbers available from your local branch.



Depending on light exposure, the product colour can vary, due to linoleum natural oxidation process. The process is reversible.

We recommend that the samples be exposed to sunlight for several hours prior to making a final color choice.

