





DESCRIPTION			
Total thickness	ISO 24346 (EN 428)	mm	2
Weight	ISO 23997 (EN 430)	g/m ²	2980
Width of sheet	ISO 24341 (EN 426)	cm	200
Length of sheet	ISO 24341 (EN 426)	lm	20
CLASSIFICATION			
Norm / Product specification	-	-	ISO 10581(EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	AS ISO 9239-1-2013	kW/m ² smoke %. min	≥10.9 157
Static electrical propensity	EN 1815	KV	<2
Electrical resistance	EN 1081	Ω	10 ⁹ -10 ¹⁰
Slip resistance dry	AS 4586 2013 (Appendix D)	class	R9
Slip resistance wet	AS 4586 2013 (Appendix A)	class	P4
PERFORMANCES			
Type binder content	ISO 10581	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	class	OK
Anti-bacterial activity (E. coli - S. aureus) (1)	JIS Z 2801		>99% Inhibits growth
Surface treatment	-	-	EASYCARE
Color number	-	-	25
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000 - 6	µg/m ³	< 10
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041		  

(1) The implementation of an effective cleaning regime is the most important defence against infections.

Gerflor has a policy of continuous product and product data improvement, it reserves the right to change design and specifications without notice.