

<b>DESCRIPTION</b>			
Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 23997	g/m <sup>2</sup>	2980
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20
<b>CLASSIFICATION</b>			
Norm / Product specification	-	-	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2
<b>PERFORMANCE</b>			
Type Binder content	EN ISO 10581	type	I
Dimensional stability	EN ISO 23999	%	≤ 0.40
Residual indentation	EN ISO 24343-1	mm	~ 0.04
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN ISO 105 - B02	degree	≥ 6
Chemical products resistance	EN ISO 26987	class	OK
Surface treatment	-	-	EASYCARE™
Colour number			22
<b>ENVIRONMENT / INDOOR QUALITY AIR</b>			
TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10
Certification			Floorscore®
<b>CE MARKING</b>			
	EN 14041	   	