

DESCRIPTION

Total thickness	EN ISO 24346 (EN 428)	mm	2
Weight	EN ISO 23997 (EN430)	kg/m ²	3.30
Width length of sheet	EN ISO 24341 (EN426)	cm/lm	200/20
Tile size	EN ISO 24342 (EN427)	mm	608 x 608
Number of tiles per package	-	-	20
Sqm/Box			7.39
Packages per pallet			34

CLASSIFICATION

Norm product specification	-	-	EN ISO 10581 (EN 649)
Fire rating	IMO Resolution		Part 5 Part 2
	Maritime Approvals		Marine Equipment Directive US Coast Guard SOLAS 74
Static electrical propensity	EN 1815	kV	< 2
Electrical resistance	EN 1081	Ω	10 ⁶ ≤ R ≤ 10 ⁸

PERFORMANCE

Wet slip resistance	EN 16165:2021 – Appendix B (DIN 51 130)	class	R9
Type binder content	ISO 10581	Type	II
Dimensional stability	EN ISO 2399 (EN 434)	%	Sheet ≤ 0.40 Tile ≤ 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≈ 0.03
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour fastness	EN 20 105 – B02	degree	≥ 6
Resistance to chemicals	EN ISO 26987 (EN 423)	-	OK
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10

