

DESCRIPTION

Total thickness	EN ISO 24346 (EN428)	mm	2
Weight	EN ISO 23997 (EN430)	kg/m ²	3.200
Width length of sheet	EN ISO 24341 (EN426)	Cm/lm	200/20
Tile size	EN ISO 24342 (EN427)	cm	60.8 x 60.8
Number of tiles per package	-	-	20
Sqm/Box			7.39
Packages per pallet			34

CLASSIFICATION

Norm product specification	-	-	EN ISO 10581 (EN 649)
Fire rating			MSC 307(88) Part 5 MSC 307(88) Part 2
	Maritime Approvals		Marine Equipment Directive US Coast Guard Transport Canada SOLAS 74
Static electrical propensity	EN 1815	kV	< 2

PERFORMANCE

Wet slip resistance	EN 16165:2021 – Appendix B (DIN 51 130)	class	R9
Type binder content	ISO 10581	Type	II
Dimensional stability	EN ISO 2399 (EN434)	%	Sheet ≤ 0.40 Tile ≤ 0.25
Residual indentation	EN ISO 24343-1 (EN433)	mm	- 0.03
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	EN 20 105 – B02	degree	≥ 6
Resistance to chemicals	EN ISO 26987 (EN 423)	-	ok
Surface Treatment	-	-	Evercare™
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10

