






DESCRIPTION	Test method	Classification standard		
Total thickness		EN ISO 24346	mm	6.00
Wearlayer thickness		EN ISO 24340	mm	2.00
Weight		EN ISO 23997	g/m ²	9240
Size		EN ISO 24342	mm	635 x 635 GTI E 5 CONNECT
				650 x 650 GTI EL5 CLEANTECH (without dove tails)
CLASSIFICATION				
Norm / Product specification		EN ISO 10582	-	-
European classification		EN ISO 10874	class	34 - 43
Fire rating		EN 13 501-1	class	Bfl-s1
Electrical resistance (1)	EN 1081	EN 14041	Ω	Rg ≤ 10 ⁶
	IEC 61340-4-1	IEC 61340-5-1		Rgp < 10 ⁹
	IEC 61.340-4-5	IEC 61340-5-1		Rg < 10 ⁹
	ANSI / ESD - STM 7.1	ANSI / ESD 20.20		Rgp < 10 ⁹
Static electrical propensity	EN 1815	EN 14041	kV	< 2
	IEC 61340-4-5	IEC 61340-5-1	V	< 100 (2)
Protection against electrostatic discharges	ANSI / ESD S20.20		-	OK
	IEC 61340-5-1		-	OK
Slip resistance wet : ramp test with oil	EN 16165:2021 – Appendix B (DIN 51 130)		class	R9
PERFORMANCES				
Wear resistance		EN 660.2	mm ³	≤ 4
Wear group		QB30	group	P
Type binder content		EN ISO 10582	type	I
Dimensional stability		EN ISO 23999	%	≤ 0.25
Shore hardness		EN ISO 868	Hd	≥ 90
Castor chair test (type W)		ISO 4918	-	OK
Thermal conductivity		EN ISO 10456	W/(m.K)	0.25
Colour fastness		EN ISO 105 - B02	degree	≥ 6
Surface treatment		-	-	Evercare™
Chemical product resistance		EN ISO 26987	class	OK
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days		ISO 16000-6	micrograms/ m ³	< 10
Certification		-	-	Floorscore®
CE MARKING				
		EN 14041	-	  
			-	

(1) Measured before installation

(2) Measured with ESD shoes (type ABEBA and Uvex)