




DESCRIPTION			
Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 23997	g/sqm	2700
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20
CLASSIFICATION			
Norm / Product specification	-	-	ISO 19322
European classification	EN ISO 10874	Class	34 - 43
Fire rating	EN 13 501-1	Class	B _{f1} -s1
Slip resistance	EN 16165:2021 – Appendix B (DIN 51 130)	Class	R10
Static electrical propensity	EN 1815	kV	< 2
PERFORMANCE			
Dimensional stability	EN ISO 23999	%	≤ 0.40
Impact sound insulation	EN ISO 717-2	dB	5
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10
Residual indentation (average measured value)	-	mm	≈ 0.04
Castor chair test (type W)	ISO 4918	-	OK
Water tightness	EN 13553 Annex A	-	pass
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN ISO 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Chemical products resistance	EN ISO 26987	class	OK
INDOOR AIR QUALITY			
VOC certifications	Blue Angel	-	ok
	Floorscore®	-	ok
	M1	-	ok
TVOC after 28 days	ISO 16000-6	Micrograms/ m ³	< 10
Anti-bacterial activity (E.coli – S. aureus – MRSA) **	ISO 22196	-	> 99 % inhibits growth
Antiviral activity (human coronavirus 229E)	ISO 21702	-	99.7% after 2h 99.9% after 5h
CIRCULAR ECONOMY			
Certification	Cradle to Cradle	level	Silver
CE MARKING			
	EN 14041	-	
		-	

The implementation of an effective cleaning method is the best defence against infection