




| DESCRIPTION | | | | | |
|--|---|--------------------|---|-------------------------|-------------------------|
| Total Thickness | EN ISO 24346 | mm | 9.5 | | |
| Weight | EN ISO 23997 | g/m ² | 9880 | | |
| Size | EN ISO 24342 | mm | 229 x 1235 | 298 x 620 | 229 x 1815 |
| Number of planks /tiles and sqm per box | - | - | 6 / 1.70 m ² | 6 / 1.11 m ² | 5 / 2.08 m ² |
| CLASSIFICATION | | | | | |
| Norm/Product Specification | - | - | EN 16511 | | |
| European Classification | EN ISO 10874 | class | 32 | | |
| Fire Rating | EN 13 501-1 | class | Bfl-s1 | | |
| Static Electrical Propensity | EN 1815 | kV | < 2 | | |
| Slip Resistance Wet | EN 16165:2021 – Appendix B (DIN 51 130) | class | R10 | | |
| PERFORMANCES | | | | | |
| Impact sound insulation | EN ISO 717-2 | dB | 16 | | |
| Dimensional Stability | EN ISO 23999 | % | ≤ 0.15 | | |
| Residual Indentation | EN ISO 24343-1 | mm | ≤ 0.10 | | |
| Castor chair test | ISO 4918 | - | OK | | |
| Thermal Conductivity | EN ISO 10456 | W/(m.K) | 0.25 | | |
| Colour Fastness | EN ISO 105 - B02 | degree | ≥ 6 | | |
| Surface Treatment | - | - | PUR+ MATT | | |
| Chemical Products Resistance | EN ISO 26987 | | OK | | |
| ENVIRONMENT / INDOOR AIR QUALITY | | | | | |
| TVOC after 28 days | ISO 16000-6 | µg/ m ³ | < 100 | | |
| CE MARKING | | | | | |
|  | EN 14041 | |  | | |
| | | |  | | |