




DESCRIPTION			
Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 23997	g/sq.m	3300
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20
Tile size	EN ISO 24342	mm	300 x 300* / 608 x 608
Number of tiles per package	-	-	50 / 20
CLASSIFICATION			
Norm / Product specification	-	-	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	B _{fl} -s1
Static electrical propensity	EN 1815	kV	≤ 2
PERFORMANCE			
Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999	%	sheet ≤ 0.40 tile ≤ 0.25
Impact sound insulation	EN ISO 717-2	dB	4
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10
Residual indentation (averagemeasured value)	-	mm	~ 0.03
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN ISO 105 - B02	degree	≥ 6
Surface treatment	-	-	PUR
Chemical products resistance	EN ISO 26987	class	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
CE MARKING			
	EN 14041	-	
		-	

* upon special request