

TRAVELLER CLASSIC LW

Technical Data Sheet

Definition	Plasticized PVC, stabilised with a glass screen, with Csi particles and PVC granules on surface. Non-woven backing.		
Presentation	. Design	Inlaid	
	. Surface texture	Calf	
	. Roll width	200 cm	
	. Roll length	12 -24 ml	
Technical characteristics	. Apparent thickness	ISO 24346	2,25 ± 0,15 mm
	. Weight per m ²	ISO 23997	2,20 ± 0,15 kg
	. Dimensional stability : 6h at 80°C	ISO 23999 ASTM D 1204	≤ 0,2 %
	. Abrasion resistance TABER - H18 wheels 1000 g 1000 g - 1000 Cycles weight loss	ISO 9352	≤ 300 mg
	. Slip resistance	DIN 51130	R10
	. Indentation test 50 daN/cm ² - 150 mm Remanent strain	ISO 24343-1	≤ 0,2 mm
	. Low temperature resistance Impact test diam. 29 mm - E = 2 joules	D 42 1235 A	- 20°C
	. Phonic insulation	ISO 717/2	ΔI = 5 dB
	. Colour fastness	ISO 877/76 ISO 4582/80	≥ 7 ≥ 3
	. Fire resistance	DIN 5510-2 BS 6853	SF3 1b
. Chemical resistance	ISO 26987	Unaffected by diluted acids and bases Unaffected by domestic products excluding solvents for plasticized PVC	