






DESCRIPTION 规格						
Total thickness 总厚度	ISO 24346 (EN 428)	mm	2.0	2.6	2.0	2.6
Wearlayer thickness 耐磨层厚度	ISO 24340 (EN 429)	mm	0.7	0.7	0.55	0.55
Weight 重量	ISO 23997 (EN 430)	g/m <sup>2</sup>	2800	3800	2900	4000
Width of sheet 卷宽	ISO 24341 (EN 426)	cm	200	200	200	200
Length of sheet 卷长	ISO 24341 (EN 426)	lm	20	15	20	15
CLASSIFICATION 类别						
Norm / Product specification 产品规范	-	-	ISO 10582 (EN 649)	ISO 10582 (EN 649)	ISO 10582 (EN 649)	ISO 10582 (EN 649)
European classification 产品分级	ISO 10874 (EN 685)	class	34-43	34-43	33-42	33-42
Fire rating 防火等级	EN 13501 - 1	class	Bfl-s1	Bfl-s1	Bfl-s1	Bfl-s1
	GB 8624 - 2012	class	B <sub>1</sub> (B-s1, t0)	B <sub>1</sub> (B-s1, t0)	B <sub>1</sub> (B-s1, t0)	B <sub>1</sub> (B-s1, t0)
Toxic testing 有毒有害物质检测	GB 18586 - 2001	-	合格	合格	合格	合格
Static electrical propensity 抗静电性	EN 1815	kV	≤ 2	≤ 2	≤ 2	≤ 2
Slip resistance wet 防湿滑性	DIN EN 16165	class	R9	R9	R9	R9
PERFORMANCES 性能						
Type binder content 粘合物分级	ISO 10582	type	I	I	I	I
Dimensional stability 尺寸稳定性	ISO 23999 (EN 434)	%	≤ 0.4	≤ 0.4	≤ 0.4	≤ 0.4
Residual indentation 残余凹陷度	ISO 24343-1 (EN 433)	mm	≤ 0.1	≤ 0.1	≤ 0.1	≤ 0.1
Castor chair test 椅子脚轮测试	ISO 4918 (EN 425)	-	OK	OK	OK	OK
Thermal conductivity 热传导性	ISO 10456 (EN 12524)	W/(m.k)	0.25	0.25	0.25	0.25
Colour fastness 颜色稳定性	ISO 105 - B02	degree	≥ 6	≥ 6	≥ 6	≥ 6
Chemical product resistance 抗化学性	ISO 26987 (EN 423)	-	OK	OK	OK	OK
Special maintenance treatment 特殊维护处理	-	-	Protecsol®	Protecsol®	Protecsol®	Protecsol®
Anti-bacterial activity 抑菌性能 (E.coli - S.aureus大肠杆菌和金黄色葡萄球菌) <sup>(1)</sup>	ISO 22196	-	> 99% inhibits growth 抑菌率	> 99% inhibits growth 抑菌率	> 99% inhibits growth 抑菌率	> 99% inhibits growth 抑菌率
Antiviral activity (human coronavirus 229E) 抗病毒活性 (人类冠状病毒229E)	ISO 21702	-	99.7% (5小时)	99.7% (5小时)	99.7% (5小时)	99.7% (5小时)
ENVIRONMENT / INDOOR AIR QUALITY 环保 / 室内空气质量						
TVOC <sub>(2)</sub> after 28 days 28天后TVOC排放量	ISO 16000 - 6	µg/m <sup>3</sup>	< 100	< 100	< 100	< 100
Certification 证书	-	-	Floorscore®	Floorscore®	Floorscore®	Floorscore®
CE MARKING 标识						
	EN 14041		 防滑  供地下暖气设备使用  抗静电  防火			

(1) The implementation of an effective cleaning regime is the most important defence against infections. 实施有效的清洁方法是抗感染最重要的防御措施。

(2) TVOC即挥发性有机化合物总排放量