






















The Cleaning frequency depends on the amount of soiling and humidity in a given area, along with the colour and pattern of the floor covering and the materials and techniques used. An effective cleaning policy should take account of these factors and specify the appropriate cleaning frequencies, equipment and techniques for the various spaces in the premises.

	Equipment used	Cleaning products	Cleaning methods
Initial or deep maintenance			
Sweeping	 Brush		FREQUENCY: As necessary
Scrubbing	 +  or  Red disk 3M or equivalent Melamine Disk  Linatex blade squeegee	 See table Dosage :  See table Melamine disk: only water	<ul style="list-style-type: none"> • Sweep • Clean with the scrubber-dryer (ensure vacuum suction is switched off), and allow the product to work for about 2 minutes • Work in strips, overlapping the lines • Complete the cleaning along the display units with the scrubbing brush and red pad • Clean the residual solution with a squeegee in areas inaccessible to the scrubber-dryer • Clean with the scrubber-dryer and vacuum <p>OR</p> <ul style="list-style-type: none"> • Sweep • Protocole finition • Clean with the scrubber-dryer + melamine disc with low speed
Finishing	 +  +  +  et 		
Routine maintenance			
Sweeping	 Brush		
Scrubbing	 +  Red disk 3M or equivalent  Bavette type Linatex	 See table Dosage :  See table	<p>FREQUENCY: Daily</p> <ul style="list-style-type: none"> • Sweep • Clean with the scrubber-dryer • Work in strips, overlapping the lines • Vacuum • Complete the cleaning along the display units using a flat applicator equipped with a microfibre cloth
Finishing	 +  + 		

Note : DO NOT USE TOO MUCH WATER ON THE FLOORING to avoid the risk of water seeping between the tiles.

Manufacturers' Contact Details		
SCRUBBER-DRYERS		
TENNANT TYPE 500	NILFISK TYPE BA651	
KARCHER TYPE B60W	HAKO TYPE TB70	
FINISHES	Imop TYPE XL	
CHEMICALS		
MANUFACTURER	INITIAL / DEEP MAINTENANCE	ROUTINE MAINTENANCE
ROCHEX	Roctonic Boosté (3%)	Roctonic Boosté (1%)
KIEHL	Dopomat Intenso (2%)	Dopomat I (0.3%)
ECOLAB	Neomat A (2-3%)	Magic Maxx (1%)
TANA	Tanex Trophy (10%)	Tanex Trophy (1-2%)
NILFISK	J25 Multi (10%)	Quick Fresh (3-5%)
KARCHER	RM 69 ASF (10%)	RM 69 ASF (0.5-1%)

If you have any questions, please do not hesitate to contact our technical department.

PREVENTIVE ACTIONS

- We advise use of the recommended detergents.
- **Dilute the products using an automatic system** (external dilution system, dilution system integrated into auto scrubber, etc.) to control consumption and minimize risks involved in handling detergents.
- **Adjust dilution to the premises** (degree of soiling, water hardness, etc.).
- If a “greasy” surface film is visible possibly due to detergent residue on the floor:
 - Check and reduce the proportion of detergent if necessary,
 - Do a clean with water only to remove the residue from the floor.
- Follow the maintenance instructions for auto scrubbers. Turn the wiper flaps regularly for **optimal suction and instantly dry surfaces**.
- Use a **PLASTIC spatula** to remove chewing gum and KIEHL’s ORANGE-PRO product (or freeze spray).
- Appropriate **White Spirit** type solvents may be used for localized and specific staining (paint, etc.) and if the detergent is ineffective.
- Liquid spills: (oil, soap, etc.):
- Immediately apply an absorbent (paper, sawdust, etc.) to the affected area. Once the liquid is absorbed, remove the absorbent then, in the case of soapy products, mechanically clean using WATER until any residue has completely disappeared (foam, etc.).
- For greasy products, before cleaning, spray a concentrated alkaline detergent over the area. Clean the area using an auto scrubber filled with WATER + DETERGENT. Repeat the operation (spray then clean) until any greasy film has completely disappeared from the surface of the floor covering.
- **Mats positioned at the entrance to premises to restrict the introduction of dirt, grit and damp can help reduce short term clean frequency and thereby preserve the appearance of flooring in the long term. For optimal entrance mat effectiveness, the standard recommendation is at least 7 metres in length and 3 different levels (coarse, medium and fine). By trapping at the entrance materials that could be dragged onto the flooring creating scratches and scuff marks where dirt can easily build up, you will help preserve the appearance of your flooring now and over time.**
- Clean entrance areas fitted with recessed GTI tiles daily to help prevent dirt being brought into the premises.

ACTIONS TO BE AVOIDED



- Never use 3M-type green, brown, black, etc. **abrasive discs** or diamond disks, etc.
- **Do not scour** (scouring pad, Scotch Brite, steel wool, etc.) or scrape (cutter, knife, glass scraper) in the case of stains or chewing gum residue.
- Do not use unsuitable corrosive solvents (acetone, etc.)
- Do not soak floors to avoid water penetration through dovetails.
- Never use melamine disks (3M or equivalent) **dry, without water**. When cleaning is completed, remove the disk from the machine and leave it to dry vertically or on a rack type system where air can circulate on both sides.