




CREATION PREMIUM LVT



CREATION PREMIUM CONSTRUCTION



PUR+MATT

Easy maintenance

4D DESIGN

MATT SURFACE

Natural look

CRYSTAL WEAR LAYER

High definition design & color

STRUCTURED EMBOSS & BEVEL

Ultra realistic surface

GRIP-WAVE BACKLAYER

ANTI-SKID BACKING

Stronger adhesion
Better acoustics
Moisture resistance

DUO CORE TECHNOLOGY

1 RESILIENT COMFORT CORE

Noise absorption

Soft underfoot

2 DOUBLE FIBREGLASS CORE

The best stability

CREATION PREMIUM DESIGNS



COGNAC OAK
1239



TOFFEE OAK
1242



PEARL OAK
1241



STRINGYBARK
1244



RIVER GUM
0162



COTTON TREE
1245



SPOTTED GUM
0389



BLACKBUTT
0387



COFFEE OAK
1240



DESERT OAK
1243

CREATION PREMIUM



SPOTTED GUM
0389



AUSTRALIAN
TIMBER
DESIGNS

CREATION PREMIUM



RIVER GUM
0162



AUSTRALIAN
TIMBER
DESIGNS

CREATION PREMIUM



BLACKBUTT
0387



AUSTRALIAN
TIMBER
DESIGNS

CREATION PREMIUM



TOFFEE OAK
1242



CREATION PREMIUM



STRINGYBARK
1244



AUSTRALIAN
TIMBER
DESIGNS

CREATION PREMIUM



COTTON TREE
1245



CREATION PREMIUM



COGNAC OAK
1239



CREATION PREMIUM



DESERT OAK
1243



CREATION PREMIUM



COFFEE OAK
1240



CREATION PREMIUM



PEARL OAK
1241



CREATION PREMIUM

Creation Premium

Gerflor's Creation Premium range of vinyl planks deliver unbeatable market leading comfort and practicality. Contemporary designs and realistic Australian timber looks feature in Creation Premium's range of durable, modular and easy to install vinyl planks. Designed for commercial and residential use, this high-quality flooring range offers both comfort and quiet with 5mm thickness and a 0.55mm wear layer in a 230 x 1500mm format.

Attention specifiers: Please register your project to ensure that we can meet your project timeline.

	CREATION PREMIUM		
DESCRIPTION			
Total thickness	EN 428	mm	5
Wearlayer thickness	EN 429	mm	0.55
Weight	EN 430	g/m ²	9020
Dimensions	EN 426	mm	230 x 1500
CLASSIFICATION			
Norm / Product specification	-	-	EN 653
European classification	EN 685	class	33-42
Fire rating	AS ISO 9239-1	kW/m ²	9.4
		smoke%/min	215
Slip resistance	AS 4586	class	R10
	AS 4586:2013	class	P3
PERFORMANCES			
Wear group	EN 660/1	-	T
Dimensional stability	EN 434	%	0.20
Residual indentation	EN 433	mm	0.05
Colour fastness	EN 20 105-B02	degree	≥ 6
Impact sound insulation	AS ISO 717.2-2004	LnTw ≤	50
Surface treatment	-	-	PUR+ Matt
VOC	ASTM D5116	mg/m ² /hr	0.035
Guarantee Residential	-	years	15
Guarantee Commercial	-	years	10
CE	EN 14041		
			

Gerflor has a policy of continuous product and product data improvement. It reserves the right to change design and specifications without notice.

Installation and Maintenance Guidelines, Complementary ranges available on our Gerflor website.
 ⚠ Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide.
 Place mats of sufficient length at entrances to reduce outside sources of dirt.

(1) For lifetime sustainable wet resistance, please refer to Creation Premium ranges.
 (2) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.

