


DESCRIPTION			
Total Thickness	EN ISO24346 (EN 428)	mm	1.5
Weight	EN ISO 23997 (EN 430)	g/m ²	300
Width	EN ISO 24341 (EN 426)	cm	118
Length	EN ISO 24341 (EN 426)	m	8.5
Packaging content		m ²	10
Packaging Weight		kg	3.5
Article code			59490001
CLASSIFICATION			
Fire rating	EN 13501-1	classe	Dfl-s1 (underlayer alone) Bfl-s1 (with homologated floors)
PERFORMANCE			
Impact sound insulation	EN ISO 717-2	dB	19 (with homologated floors)
Thermal resistance	EN 12664	m ² K/W	0.04
Compressive Strength	EN ISO 3386 / EN826	kPa	400
Compressive Strength	EN ISO 3386 / EN826	t/m ²	40
Punctual Conformability	CEN/TS 16354	mm	~ 0.9
			

This product is recommended by Gerflor for the following products:

- CREATION 30 SOLID CLIC
- CREATION 40 SOLID CLIC
- CREATION 55 SOLID CLIC
- SENSO PREMIUM CLIC 2
- SENSO CLIC 2
- SENSO CLIC
- LOCK+ 30 (For classe 23 use only)
- LOCK+55 (For classe 23 use only)
- SENSO 20 LOCK (For classe 22 use only)
- RIGID 30 LOCK (For classe 22 use only)

It is not suitable for industrial or semi-industrial application