

DESCRIPTION

Total thickness	ISO 24346 (EN 428)	mm	5
Wearlayer thickness	ISO 24340 (EN 429)	mm	1
Weight	ISO 23997 (EN 430)	g/m ²	7460
Tile size	ISO 24342 (EN 427)	mm	635 x 635 Connect 600 x 600 Cleantech (without

CLASSIFICATION

Norm / Product specification	-	-	ISO 10582 (EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501 - 1	class	Bfl-s1
	GB 8624	class	B1
Toxic testing	GB 18586	-	OK
Slip resistance wet	DIN EN16165 annex B (DIN 51130)	class	R10



PERFORMANCES

Type binder content	ISO 10582	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.25
Residual indentation	ISO 24343-1 (EN 433)	mm	≤ 0.10
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.k)	≈ 0.25
Colour fastness	ISO 105-B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK
Surface treatment	-	-	Protecsol®2

ENVIRONMENT / INDOOR AIR QUALITY

Certification	-	-	Floorscore®
---------------	---	---	-------------

CE MARKING

	<p>EN 14041</p>	
---	-----------------	---