
			GTI MAX CONNECT	GTI MAX CLEANTECH
DESCRIPTION				
Total thickness	ISO 24346 (EN 428)	mm	6	6
Wearlayer thickness	ISO 24340 (EN 429)	mm	2	1
Weight	ISO 23997 (EN 430)	g/m ²	9365	8935
Tile size	ISO 24342 (EN 427)	mm	635 x 635	600x600 (without dovetail)
CLASSIFICATION				
Norm / Product specification	-	-	ISO 10582 (EN 649)	ISO 10582 (EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43	34 - 43
Fire rating	EN 13501 - 1	class	Bfl-s1	Bfl-s1
	GB 8624	class	B1	B1
Toxic testing	GB 18586	-	OK	OK
Slip resistance wet	DIN EN16165 annex B (DIN 51130)	class	R10	R10
PERFORMANCES				
Type binder content	ISO 10582	type	I	I
Dimensional stability	ISO 23999 (EN 434)	%	< 0.15	< 0.15
Residual indentation	ISO 24343-1 (EN 433)	mm	≤ 0.10	≤ 0.10
Castor chair test	ISO 4918 (EN 425)	-	OK	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.k)	≈ 0.25	≈ 0.25
Colour fastness	ISO 105-B02	degree	≥ 6	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK	OK
Surface treatment	-	-	PUR+	PUR+
ENVIRONMENT / INDOOR AIR QUALITY				
Certification	-	-	Floorscore®	Floorscore®
CE MARKING				
		EN 14041	