




RIGID 55 LOCK





RIGID 55 LOCK



LOCKING SYSTEM



NO ADHESIVE REQUIRED



DIMENSIONAL STABILITY



SUPERIOR DURABILITY



ULTRA REALISTIC



EASY MAINTENANCE



INDENTATION RESISTANCE

The **Virtuo Rigid 55 Lock** draws on the very latest hybrid technological innovations to deliver the ultimate in residential flooring. Realistic timber finishes reflect the very latest international design trends and classic Australian timbers. These stylish good looks combined with a heavy duty 0.55mm wearlayer to answer the demands of busy family life. The extruded core technology achieves market leading dimensional stability wherever you are in Australia's varied climate. The Unilin interlocking system further enhances these solid credentials.

Both beautiful and tough, Virtuo Rigid 55 Lock is guaranteed to support your family for a minimum of 15 years.



* Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure or for compensation for any other loss or damage. You are also entitled to have the goods repaired if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

For more details call 1800 060 785 or visit gerflor.au

COLLECTION

PUNO BROWN
0016

PUNO PURE
0017

KILDA CASHMERE
0018

LOVINA
0879

YARRA COFFEE
0880

SOVEREIGN BLACKBUTT
3004

VENERABLE BLACKBUTT
3005

OCEAN VIEW SPOTTED GUM
3006

OCEAN VIEW
SPOTTED GUM
3006

Advanced printing
technology delivers
a realism that is
indistinguishable from
timber flooring.



ULTRA
REALISTIC

PUNO
BROWN
0016

With reinforced heavy
duty wear layer this is
perfect for the busiest
of households.



SUPERIOR
DURABILITY



PUNO
CLEAR
0017

VENERABLE
BLACKBUTT
3005

The superior surface
treatment makes
cleaning effortless.



EASY
MAINTENANCE



LOVINA
0879

Unilin locking system
allows the planks to
be installed quickly
without the need for
adhesive.



NO ADHESIVE
REQUIRED



YARRA
COFFEE
0880

With an extruded core
this floor can withstand
our varied climate no
matter where you live
in Australia.



DIMENSIONAL
STABILITY



SOVEREIGN
BLACKBUTT
3004



KILDA
CASHMERE
0018



High resistance to scratch and indentation making it perfect for high traffic areas.



INDENTATION
RESISTANCE

VIRTUO RIGID 55 LOCK SPECIFICATIONS	STANDARD	UNIT OF MEASURE	
THICKNESS	ISO 24346	mm	6
WEAR LAYER THICKNESS	ISO 24340	mm	0.55
DIMENSIONS	ISO 24342	mm	224 × 1525
AREA PER BOX		m ²	1.71
PLANKS PER BOX		qty	5
SLIP RESISTANCE	AS 4586	class	R10
	AS 4586:2013	class	P3
FIRE RATING	AS ISO 9239-1	kW / m	29.0
		smoke% / min	126
VOLATILE ORGANIC COMPOUNDS [VOC]	ASTM D5116	mg/m3/hr (24hrs)	Extremely low



COVER IMAGE: LOVINA (1079)

gerflor.au | 1800 060 785



VIEW IMAGES
OF THE VIRTUO
RANGE

