



GTI PURE CONNECT

DESCRIPTION	STANDARDS	REQUIREMENTS	GTI PURE CONNECT
PRODUCT DESCRIPTION			
Reference Specification*	ASTM F1700	-	Meets Performance Requirements
Construction	-	-	Interlocking Technical Tile with Soft Emboss
Surface Treatment/Maintenance	-	-	PUR+
Gauge Total Thickness	ASTM F386	> 0.075"	0.24" (6.0 mm)
Tile Size	-	-	With Dove Tails: 25" x 25" (635 mm x 635 mm)
PERFORMANCE			
Static Load Resistance	ASTM F970	≤ 0.005"	Meets Requirements
Abrasion	ASTM F510	-	Meets Requirements
Rolling Load Test	ASTM F2753	-	Meets Requirements
Chemical & Stain Resistance	ASTM F925	-	Meets Requirements
Coefficient of Friction	ASTM D2047	-	Meets Requirements
Indentation - Hardness	ASTM D2240	-	95
Smoke Density (Flaming and Non-Flaming)	ASTM E662	-	Meets Requirements
Fire Rating - Flame Spread	ASTM E648	Class 1	Meets Requirements
ENVIRONMENT HEALTH & SAFETY			
Bacterio-Static**	ISO 22196	-	Inhibits spread of infections at 99%
Viro-Static**	ISO 21702	-	Inhibits growth of virus of 99.7% after 2 hours
Manufacturing Plant Certifications	ISO 9001, 14001, 45001, 50001	-	Quality, Environment, Health & Safety, Energy
Environmental Product Declaration (EPD)	LEED v4 M+R	-	Product-Specific Type III
Material Ingredients: Health Product Declaration (HPD)	LEED v4 M+R	-	Self-Declared
No Harmful Chemicals	European Chemicals Agency (ECHA)	-	100% REACH Compliant
Sourcing of Raw Material: Recycled Content	Average Pre-Consumer Content	-	57%
Indoor Air Quality	California Standard 01350	-	FloorScore® Certified
Production Waste	In-Plant Recycling	-	100% Manufacturing Waste Recycled
TVOC after 28 days	ISO 16000-6	-	≤10µg/m ³
Embodied Carbon	kg/CO ² /m ²	-	19.1 kg CO ² /m ²
WARRANTY	10-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on gerflorusa.com		

*Rubber leaves indelible stains on synthetic floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

** The best defense against the spread of infections is the implementation of an effective cleaning method.