




DESCRIPTION 规格			
Total thickness 总厚度	EN ISO 24346	mm	2.00
Width of sheet 卷宽	EN ISO 24341	cm	200
Length of sheet 卷长	EN ISO 24341	lm	20
Coverage / roll 面积/卷	-	sq.m	40
Tile size 片材尺寸	EN ISO 24342	mm	608 x 608 *
Number of tiles per package 片材数量/每箱	-	-	20
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	EN ISO 10581
European classification 产品分级	EN ISO 10874	class	34 - 43
Fire rating 防火等级	EN 13 501-1	class	B _{fl-s1}
	GB 8624-2012	class	B ₁
Static electrical propensity 静电测试性能	EN 1815	kV	≤2
PERFORMANCE 性能			
Type Binder content 粘合剂分级	EN ISO 10581	type	I
Dimensional stability 尺寸稳定性	EN ISO 23999	%	≤ 0.40
Residual indentation (norm) 残余凹陷度	EN ISO 24343-1	mm	≤ 0.10
Castor chair test 椅子脚轮测试	ISO 4918	-	OK
Thermal conductivity 热传导性	EN ISO 10456	W/(m.K)	0.25
Colour fastness 色牢度	EN ISO 105-B02	degree	≥ 6
Surface treatment 特殊维护处理	-	-	Evercare™
Chemical products resistance 抗化学性	EN ISO 26987	class	OK
Anti-bacterial activity 抑菌性能 (E.coli – S. aureus 大肠杆菌和金黄色葡萄球菌) *	ISO 22196	-	> 99 % 抑菌率
Antiviral activity (human coronavirus 229E) 抗病毒活性 (人类冠状病毒229E)	ISO 21702		2小时后99.7%
ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量			
TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/ m³	< 10
Certification 证书	-	-	Floorscore®
	GB 18586-2001		OK
CE MARKING 标识			
	EN 14041	-	 防火  供地下暖气设备使用  防滑  抗静电

*Products available in tiles for a minimum quantity order of 500sqm. 片材的最小起订量为500m²。

**The implementation of an effective cleaning method is the best defence against infection. 实施有效的清洁方法是抗感染最重要的防御措施。