

	Mipolam 美宝琳 Planet R10		
DESCRIPTION 规格			
Total thickness 总厚度	EN ISO 24346	mm	2.00
Width of sheet 卷宽	EN ISO 24341	cm	200
Length of sheet 卷长	EN ISO 24341	lm	20
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	EN ISO 10581
European classification 产品分级	EN ISO 10874	class	34 - 43
Fire rating 防火等级	EN 13 501-1	class	B _{fl} s ¹
	GB 8624-2012	class	B ₁
Static electrical propensity 静电测试性能	EN 1815	kV	≤2
PERFORMANCE 性能			
Type Binder content 粘合物分级	EN ISO 10581	type	I
Dimensional stability 尺寸稳定性	EN ISO 23999	%	≤ 0.40
Residual indentation (norm) 残余凹陷度	EN ISO 24343-1	mm	≤ 0.10
Slip resistance 防湿滑性	DIN EN 16165 annex B (DIN 51130)	Class	R10
Castor chair test 椅子脚轮测试	ISO 4918	-	OK
Colour fastness 色牢度	EN ISO 105-B02	degree	≥ 7
Surface treatment 特殊维护处理	-	-	Evercare™
Chemical products resistance 抗化学性	EN ISO 26987	class	OK
Anti-bacterial activity 抑菌性能 (E.coli – S. aureus 大肠杆菌和金黄色葡萄球菌) *	ISO 22196	-	> 99 % 抑菌率
Antiviral activity (human coronavirus 229E) 抗病毒活性 (人类冠状病毒229E)	ISO 21702		2小时后99.7% 5小时后99.9%
ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量			
TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/ m ³	< 10
Certification 证书	-	-	Floorscore®
	GB 18586-2001		OK
CE MARKING 标识			
	EN 14041	-	    防火 供地下暖气设备使用 防滑 抗静电

* The implementation of an effective cleaning method is the best defence against infection. 实施有效的清洁方法是抗感染最重要的防御措施。