



Mipolam Planet

Homogeneous Flooring

Gerflor[®]

Mipolam® Planet

The Original Mipolam 1937



Specifications have been built on Gerflor for over 80 years. Mipolam, the original homogeneous sheet flooring since 1937, is still the most durable of its category with a life expectancy of over 20 years. A legacy of invention and a commitment to innovation ensures that Mipolam Planet provides the best performance in demanding healthcare environments.



Gerflor healthcare solutions are intentionally designed for coordination across a variety of products. Every range and color line is designed to seamlessly blend and enhance the space while allowing you to meet specification requirements.

Mipolam Planet

Durable construction for demanding and high traffic environments



Heavy traffic resistance

EVERCARE™

Ease of maintenance thanks to Evercare™

40
colors

Bright and subtle non-directional design



6'6" x 66' rolls



5409 Pebble Beach & 5413 Rain Fall



An innovative corner system serving hygiene



Patented Gerflor Exclusive System

Suitable for all Gerflor VINYL floors. Clean Corner System enables corners to meet all healthcare & industry requirements.

- 1) Clean Corner internal floor angle
- 2) Clean Corner external floor angle



An exclusive Gerflor patented treatment. Excellent performance:

1

Stain Shield



2

No wax for life
Water and detergent savings



3


Matte finish: enhanced design & color, long-lasting appearance




4

Hygiene: Inhibits spread of infections at 99% and growth of viruses at 99.7% after 2 hours
ISO 22196 and ISO 21702






5412 Moon Stone



5424 Hawk Eye




5402 Ivory Dust




5475 Intense Ruby



5403 Moon Dust




5455 Lava Flow




5427 Green Zest




5432 Sun Stone




5422 Sunflower




5447 Aventurine




5417 Foggy Hill




5406 Moqui




5482 Sugar Drip




5426 Shadow




5456 Intense Indigo




5466 Rocky Blue




5416 Acquamarina




5446 Blue Nug




5436 Tiger Eye




5437 Reef Water



5408 Chalk Dust




5429 Fog Patch




5410 Silex




5409 Pebble Beach




5459 Stormy Cloud




5460 Lava Stone




5413 Rain Fall




5411 Atlantic Grey




5450 Blended Ashes




5420 Stone Powder




5428 Shedded Ground




5444 Rocky Hill




5445 Tree Bark




5443 Wood Path




5418 Terra Nerra




5438 Andalusite



5441 Clay Soil



5430 Sideral Grey



5439 Moon Way



5404 Vanilla Sky



GERFLOR USA
877-437-3567
info@gerflorusa.com
gerflorusa.com



GENA0143

DESCRIPTION	STANDARDS	REQUIREMENTS	MIPOLAM PLANET
PRODUCT DESCRIPTION			
Reference Specification*	ASTM F1913	-	Meets Performance Requirements
Construction	-	-	Homogeneous Sheet Flooring
Surface Treatment / Maintenance	-	-	Evercare® / No wax for life
Gauge Total Thickness	ASTM F386	> 0.075"	0.08" (2.0 mm)
Roll Width	-	-	6' 6" (2.0 m)
Roll Length	-	-	66' (20 m)
Coverage / Roll	-	-	430.6 ft ² (40 m ²)
Weight	-	-	0.55 lb/ft ² (2700 g/m ²)
PERFORMANCE			
Static Load Resistance	ASTM F970	≤ 0.005"	Meets Requirements
Abrasion	ASTM F510	-	Meets Requirements
Indentation - Residual	ASTM F1914	≤ 0.007"	Meets Requirements
Flexibility	ASTM F137	> 1.5"	Meets Requirements
Chemical & Stain Resistance	ASTM F925	-	Meets Requirements
Resistance to Heat	ASTM F1514	ΔE ≤ 8	Meets Requirements
Resistance to Light	ASTM F1515	ΔE ≤ 8	Meets Requirements
Coefficient of Friction	ASTM D2047	-	0.56 dry
Fire Rating (Flaming and Non-Flaming)	ASTM E662	-	Meets Requirements
ENVIRONMENT HEALTH & SAFETY			
Bacterio-Static**	ISO 22196	-	Inhibits spread of infections at 99%
Viro-Static**	ISO 21702	-	Inhibits growth of virus of 99.7% after 2 hours
Manufacturing Plant Certifications	ISO 9001, 14001, 45001, 50001	-	Quality, Environment, Health & Safety, Energy
Environmental Product Declaration (EPD)	LEED v4 M+R	-	Product-Specific Type III
Material Ingredients: Health Product Declaration (HPD)	LEED v4 M+R	-	Self-Declared
Sourcing of Raw Material: Recycled Content	Average Pre-Consumer Content	-	25%
Indoor Air Quality	California Standard	-	FloorScore® Certified
Production Waste	In-Plant Recycling	-	100% Manufacturing Waste Recycled
TVOC after 28 days	ISO 16000-6	-	<10µg/m ³
WARRANTY	10-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on gerflorusa.com		

*Rubber leaves indelible stains on synthetic floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

** The best defense against the spread of infections is the implementation of an effective cleaning method. For the most updated documentation and specification content, please visit gerflorusa.com

MIPOLAM PLANET USA Binder - 2024

