

## **TEST REPORT**

DATE: 12-03-2024	Page 1 of 1	<b>TEST NUMBER</b> : 0312555
CLIENT	Gerflor The Flooring Group - France	
TEST METHOD CONDUCTED ASTM F1514 Measuring Heat Stability of Resilient F   Change Change		y of Resilient Flooring by Color
DESCRIPTION OF TEST SAMPLE		
IDENTIFICATION	Taraflex Sport M+	

## **GENERAL PRINCIPLE**

The test specimens are exposed to heat for 7 continuous days in an air circulating chamber. The materials are read using a spectrophotometer for the baseline color value and then read after the exposure. The Delta E is listed to show the color value change resulting from each exposure.

## TEST RESULTS

	DELTA E (AE) Rating	Gray Scale Rating
Heat Aged Sample 1	0.62	5.0
Heat Aged Sample 2	0.43	5.0
Heat Aged Sample 3	0.75	5.0

AVERAGE RATING	0.60	5.0
MAXIMUM RATING	0.75	5.0

Test requirements of < 8.0 Delta E were met by the tested samples.

AATCC RATING KEY		
5	No change	
4	Slight change	
3	Noticeable change	
2	Considerable change	
1	Severe change	

APPROVED BY:

hillips le

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical or similar products. This report, or the name of Professional Testing Laboratory, LLC, shall not be used under any circumstance in advertising to the general public.