

	RECREATION LEISURE 45 乐境 45			
	Uni/ Wood 纯色/ 木纹			
	PRODUCT CHARACTERISTICS 产品特性			
	Standard 标准	Requirement 要求	Unit 单位	Results 结果
	PRODUCT DESCRIPTION 产品规格			
Surface treatment 表面处理	-	-	-	PUR PROTECT
Foam 泡沫背层	-	-	-	Closed cell foam 密闭式泡沫背层
Thickness 厚度	ISO 24346	-	mm	4.5
Weight 重量	ISO 23997	-	kg/m2	2.8
Length 长度	ISO 24341	-	lm	20.5
Width 宽度	ISO 24341	-	m	2
	SPORT PROPERTIES 运动特性			
Vertical deformation 垂直变化值	EN 14809	≤ 5.0	mm	≤ 3.5
Sliding coefficient 滑动系数	EN 13036-4	80 to 110	-	80 to 110
Ball bounce 球类反弹	EN 12235	≥ 90	%	≥ 90
	TECHNICAL CHARACTERISTICS 技术特性			
Abrasion resistance 耐磨性	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance 抗冲击性	EN 1517	≥ 8	Nm	≥ 8
Indentation resistance 残余凹陷度	EN 1516	≤ 0.5	mm	≤ 0.5
	CLASSIFICATION 分类			
TVOC after 28 days 28天后TVOC排放量 (1)	ISO 16000-6	µg/m3	< 100	< 100
Toxic testing 有毒有害物质检测	GB 18586-2001	-	-	合格
Certification 证书	-	-	-	Floorscore®
Fire resistance 防火性能	GB 8624-2012	-	-	B1
Anti-bacterial activity 抗菌性能 (2)	ISO 22196	-	-	> 99% 24H
Anti-viral activity 抗病毒性能	ISO 21702	-	-	> 99% 24H
	DECLARATION OF PERFORMANCE 产品性能声明			
	EN14904	-	Fire 防火 Sliding Coefficient 滑动系数 Abrasion Resistance 耐磨性 Resistance to rolling load 抗滚动载荷	



Health & Safety



ISO 14001



Recycling

(1)TVOC:挥发性有机化合物总排放量。

(2)The implementation of an effective cleaning regime is the most important defence against infections.实施有效的清洁方法是抗感染最重要的防御措施。