
	<b>RECREATION LEISURE 45</b>			
	<b>Uni/ Wood</b>			
	<b>PRODUCT CHARACTERISTICS</b>			
	<b>Standard</b>	<b>Requirement</b>	<b>Unit</b>	<b>Results</b>
	<b>PRODUCT DESCRIPTION</b>			
Surface treatment	-	-	-	PUR PROTECT
Foam	-	-	-	Closed cell foam
Thickness	ISO 24346	-	mm	4.5
Weight	ISO 23997	-	kg/m2	2.8
Length	ISO 24341	-	lm	20.5
Width	ISO 24341	-	m	2
	<b>SPORT PROPERTIES</b>			
Vertical deformation	EN 14809	≤ 5.0	mm	≤ 3.5
Sliding coefficient	EN 13036-4	80 to 110	-	80 to 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
	<b>TECHNICAL CHARACTERISTICS</b>			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	Nm	≥ 8
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
	<b>CLASSIFICATION</b>			
TVOC after 28 days	ISO 16000 - 6	µg/m3	< 100	< 100
Certification	-	-	-	Floorscore®
Fire resistance	EN 13501 - 1	-	-	Cfl - s1
Anti-bacterial activity (1)	ISO 22196	-	-	> 99% 24H
Anti-viral activity	ISO 21702	-	-	> 99% 24H
	<b>DECLARATION OF PERFORMANCE</b>			
	EN14904	-	Fire Sliding Coefficient Abrasion Resistance Resistance to rolling load	



Health & Safety



ISO 14001



Recycling

(1) The implementation of an effective cleaning regime is the most important defence against infections.