
	RECREATION LEISURE 65			
	Uni/ Wood			
	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
	PRODUCT DESCRIPTION			
Surface treatment	-	-	-	PUR PROTECT
Foam	-	-	-	Closed cell foam
Thickness	ISO 24346	-	mm	6.5
Weight	ISO 23997	-	kg/m2	4
Length	ISO 24341	-	lm	20.5
Width	ISO 24341	-	m	2
	SPORT PROPERTIES			
Shock absorption	EN 14808	-	%	≥ 25
Vertical deformation	EN 14809	≤ 5.0	mm	≤ 2.0
Sliding coefficient	EN 13036-4	80 to 110	-	80 to 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
	TECHNICAL CHARACTERISTICS			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	Nm	≥ 8
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
	CLASSIFICATION			
TVOC after 28 days	ISO 16000-6	µg/m3	< 100	< 100
Certification	-	-	-	Floorscore®
Fire resistance	EN 13501-1	-	-	Cfl - s1
Anti-bacterial activity (1)	ISO 22196	-	-	> 99% 24H
Anti-viral activity	ISO 21702	-	-	> 99% 24H
	DECLARATION OF PERFORMANCE			
	EN14904	-	Fire Sliding Coefficient Abrasion Resistance Resistance to rolling load	



(1) The implementation of an effective cleaning regime is the most important defence against infections.