






DESCRIPTION			
Total thickness	EN ISO 24346	mm	2.00
	ASTM F386-02	inch	0.08
Weight	EN ISO 23997	g/sq.m	3300
Width of sheet	EN ISO 24341	cm	200
	-	Feet-inch	6'6"
Lenght of sheet	EN ISO 24341	lm	20
	-	Feet-inch	66'
Tile size	EN ISO 24342	mm	608 x 608
Number of tiles per box	-	-	20
CLASSIFICATION			
Norm / Product Specification	-	-	EN ISO 10581
	ASTM F 1913-04		compliant
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	B <sub>fl</sub> -s1
	ASTM E648-08	class	Class I
	CAN /ULCS102.2	-	tested in accordance
Static electrical propensity	EN 1815	kV	≤ 2
Slip resistance wet	EN 16165:2021 – Appendix B (DIN 51 130)	class	R9
PERFORMANCE			
Type binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999	%	sheet ≤ 0.40 tile ≤ 0.25
Impact sound insulation	EN ISO 717-2	dB	4
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10
Residual indentation (average measured value)	-	mm	~ 0.03
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN ISO 105 - B02	degree	≥ 7
Surface treatment	-	-	Evercare™
Chemical products resistance (1)	EN ISO 26987		OK
Anti-bacterial activity (E. coli – S.aureus – MRSA) (2)	ISO 22196	-	> 99 % inhibits growth
Antiviral activity (human coronavirus 229E)	ISO 21702		99.7% after 2h
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10
Certification			Floorscore®
CE MARKING			
	EN 14041	-	  
		-	

- (1) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.  
(2) The implementation of an effective cleaning method is the best defence against infection.