Inosa
 0002 Gr

 Straw
 0033 f

 Berry
 0003 Gr

 Berry
 0003 Gr

 actta
 0003 Gr

 Poppy
 0033 Gr

 Poppy
 0034 Gr

 Poppy
 0035 Bas

 Poppy
 0036 Bas

 Poppy
 0006 F

 Poppy
 0000 S

 Point
 0000 S

## **PROTECTA 2** VARIABLE ANGLE FLEXIBLE ADHESIVE CORNER PROTECTOR

102 Spum



## APPLICATIONS .....

Thanks to its rounded, reinforced flexible strip, this product provides efficient, decorative and economical protection for all corners exposed to frequent impact.

Available in 39 colours, this model blends in with all interior decoration styles in public buildings.

## DESCRIPTION .....

- Model: Protecta 2 flexible adhesive corner protector
- Angle: from 50° to 155°
- Wing width: 60 mm (internal measurement)
- Thickness: 2 mm
- Length: 1.30 m, 2.00 m or 4.00 mMaterial: antibacterial and Bs2d0
- fire-rated PVC, solid colour

6⁄0

- Surface finish: smooth
- Fixing: adhesive foam tapes to reinforce with SPM multipurpose adhesive sealant
- Colours: 39

Adhesive foam


Variable angle

from 50° to 155°

t/ape

## SPECIFICATION .....

- Description: variable angle adhesive corner protector (from 50° to 155°) with flexible strip (Protecta 2 as manufactured by SPM) from smooth and antibacterial PVC, 2 mm thick, achieving Bs2d0 reaction to fire classification with solid colour. Wings are 60 mm wide (internal measurement) and the central rounded bead forms a decorative and harmless strip. A protective film is specified to minimise cleaning before acceptance. It is provided with 2 strips of double-sided adhesive foam tape for fixing.
- Environment: no heavy metals and no substance potentially subjected to any REACH restriction are used in its manufacture, nor PBT/BPA. The calcium-zinc thermal stabilisation process is used. The emission level of volatile substance in inside air has been tested according to ISO 16000-6 and is very low (A+) according to the French regulation (23 March 2011 nr 2011-321 Decree and 19 April 2011 Order). 100% of the product are recyclable.
- Colour: selected by architects from manufacturer's standard range.
- Installation method: adhesive. SPM multipurpose adhesive sealant is recommended for stronger fixing.



Specifications and section drawings on our website www.spm-international.com



Śol/d doldur/and / antibacterial smooth PVC 2 mm thick

> Wall protections and handrails Tel. : +33 (0)5 34 39 41 00 export@spm.fr

www.spm-international.com

A company of Gerflor