

| DESCRIPTION                                                                        | Osmoz – Indiana – Metallica – Brazilia – Poesy – Neopolis – Cocoon – Neoterra |                                                                                                                                                                                                                                                                   |                                                                                           |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Total thickness                                                                    | EN ISO 24346                                                                  | mm                                                                                                                                                                                                                                                                | 3.00-3.30                                                                                 |
|                                                                                    | ASTM F386-02                                                                  | inch                                                                                                                                                                                                                                                              | 0.12 - 0.13                                                                               |
| Wearlayer thickness                                                                | EN ISO 24340                                                                  | mm                                                                                                                                                                                                                                                                | ≥ 1.02                                                                                    |
|                                                                                    | ASTM F410-02                                                                  | inch                                                                                                                                                                                                                                                              | ≥ 0.039                                                                                   |
| Weight                                                                             | EN ISO 23997                                                                  | g/sq.m                                                                                                                                                                                                                                                            | ≥ 2800                                                                                    |
|                                                                                    | -                                                                             | lbs/sq.ft                                                                                                                                                                                                                                                         | 0.58                                                                                      |
| Width of sheet                                                                     | EN ISO 24341                                                                  | cm                                                                                                                                                                                                                                                                | 200                                                                                       |
|                                                                                    | -                                                                             | feet - inch                                                                                                                                                                                                                                                       | 6'6"                                                                                      |
| Length of sheet                                                                    | EN ISO 24341                                                                  | lm                                                                                                                                                                                                                                                                | 25                                                                                        |
|                                                                                    | -                                                                             | feet - inch                                                                                                                                                                                                                                                       | 82'                                                                                       |
| CLASSIFICATION                                                                     |                                                                               |                                                                                                                                                                                                                                                                   |                                                                                           |
| Norm / Product specification                                                       | -                                                                             | -                                                                                                                                                                                                                                                                 | NF EN ISO 11638                                                                           |
| European classification                                                            | EN ISO 10874                                                                  | class                                                                                                                                                                                                                                                             | 34 -42                                                                                    |
| Fire rating                                                                        | EN 13 501-1                                                                   | class                                                                                                                                                                                                                                                             | Cfl-s1                                                                                    |
| Static electrical propensity                                                       | EN 1815                                                                       | kV                                                                                                                                                                                                                                                                | < 2                                                                                       |
| Slip resistance (1)                                                                | EN 16165:2021<br>Appendix B<br>(DIN 51 130)                                   | class                                                                                                                                                                                                                                                             | R10                                                                                       |
| PERFORMANCES                                                                       |                                                                               |                                                                                                                                                                                                                                                                   |                                                                                           |
| Wear resistance                                                                    | EN 660.2                                                                      | mm <sup>3</sup>                                                                                                                                                                                                                                                   | < 2.0                                                                                     |
| Wear group                                                                         | -                                                                             | group                                                                                                                                                                                                                                                             | T                                                                                         |
| Dimensional stability                                                              | EN ISO 23999                                                                  | %                                                                                                                                                                                                                                                                 | ≤ 0.40                                                                                    |
| Residual indentation (requirement)                                                 | EN ISO 24343-1                                                                | mm                                                                                                                                                                                                                                                                | ≤ 0.20                                                                                    |
| Residual indentation (measure)                                                     | -                                                                             | mm                                                                                                                                                                                                                                                                | ≈ 0.06                                                                                    |
| Impact sound insulation                                                            | EN ISO 717-2                                                                  | dB                                                                                                                                                                                                                                                                | 17 ( Osmoz – Indiana– Brazilia – Poesy – Neopolis – Cocoon – Neoterra )<br>16 (Metallica) |
| Castor chair test (type W)                                                         | ISO 4918                                                                      | -                                                                                                                                                                                                                                                                 | OK                                                                                        |
| Thermal conductivity                                                               | EN ISO 10456                                                                  | W/(m.K)                                                                                                                                                                                                                                                           | 0.25                                                                                      |
| Colour fastness                                                                    | EN ISO 105 - B02                                                              | degree                                                                                                                                                                                                                                                            | ≥ 6                                                                                       |
| Surface treatment                                                                  | -                                                                             | -                                                                                                                                                                                                                                                                 | Evercare™                                                                                 |
| Chemical products resistance (2)                                                   | EN ISO 26987                                                                  | -                                                                                                                                                                                                                                                                 | OK                                                                                        |
| Anti-bacterial activity (E. coli - S. aureus - MRSA) (3)                           | ISO 22196                                                                     | -                                                                                                                                                                                                                                                                 | > 99 % inhibits growth                                                                    |
| Anti-Viral activity (human coronavirus 229E) (3)                                   | ISO 21702                                                                     | -                                                                                                                                                                                                                                                                 | > 99,7% after 2 hours                                                                     |
| ENVIRONMENT / INDOOR AIR QUALITY                                                   |                                                                               |                                                                                                                                                                                                                                                                   |                                                                                           |
| TVOC after 28 days                                                                 | ISO 16000-6                                                                   | µg/m <sup>3</sup>                                                                                                                                                                                                                                                 | < 10                                                                                      |
| Certification                                                                      | -                                                                             | -                                                                                                                                                                                                                                                                 | Floorscore®                                                                               |
| CE MARKING                                                                         |                                                                               |                                                                                                                                                                                                                                                                   |                                                                                           |
|  | <b>EN 14041</b>                                                               |    |                                                                                           |
|                                                                                    |                                                                               |                                                                                                                                                                              |                                                                                           |

(1) For lifetime sustainable wet resistance, please refer to Tarasafe ranges.

(2) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.

(3) The implementation of an effective cleaning regime is the most important defence against infection.