

# REACTION TO FIRE CLASSIFICATION REPORT N°2025/103-2

(English version of classification report N°2025/103-1)

According to EN 13501-1 (2018)

Notification by the French Government to the European Commission under n° NB 2401

Regulation (UE) n° 305/2011

Sponsor:

**GERFLOR** 

1 Place Verrazzano

69258 LYON Cedex 09

**FRANCE** 

Product name:

**ARMONIA 520** 

Description:

Textile floor covering (EN 1307 family)

(see detailed description in paragraph 2)

Date of issue:

10/06/2025

The indicated classification does not prejudge the conformity of marketed materials with the samples submitted to the tests and under no circumstances, this document should not be considered as type approval or certification of the product in the sense of the L 115-27 article of the consumption's code of the law.

The reproduction of this classification report is only authorised in its integral form. It comprises 3 pages

#### 1. Introduction

This classification report defines the classification assigned to the above-mentioned product in accordance with the procedures given in the NF EN 13501-1 standard (2018).

#### 2. Details of classified product

### 2.1. Product standard

NF EN 14041 (2005): "Resilient, textile and laminate floor coverings - Essential characteristics".

#### 2.2. Product description

Tufted loop pile carpet tile of 50 cm x 50 cm with tonal effect on bitumen backing (EN 1307 family).

Tested loose laid over a wood panel particle board without flame retarded classified  $C_{fl}$ -s1 with a density (680  $\pm$  50) kg/m<sup>3</sup> and thickness (20  $\pm$  2) mm.

Use surface: 100% polyamide

Nominal mass per unit area: 4000 g/m<sup>2</sup> Nominal total thickness: 5,6 mm Nominal pile thickness: 2,4 mm

## 3. Test reports and tests results in support of this classification

## 3.1. Tests reports

Name of laboratory	Name of sponsor	Test report N°	Test method
C.R.E.T.	GERFLOR	RL 2025/338-1	NF EN ISO 9239-1
	1 Place Verrazzano	KL 2023/338-1	(EN ISO 9239-1: 2010)
	69258 LYON Cedex 09	DI 2025/229 2	NF EN ISO 11925-2
	FRANCE	RL 2025/338-2	(EN ISO 11925-2: 2020)

#### 3.2. Tests results

			Results	
Test method	Product	Number of tests	Parameters	Compliance parameters
NF EN ISO 11925-2	ARMONIA 520		Fs ≤ 150 mm	Compliant
Surface exposure-15 secondes		6	Ignition of the filter paper	Compliant

				Results
Test method	Product	Number of tests	Parameters	Continuous parameters: mean value
NF EN ISO 9239-1	ARMONIA 520	3	Critical heat flux (kW/m²)	4,5
			Smoke (% X min)	381,4

#### 4. Classification and field of application

#### 4.1. Reference of classification

This classification has been carried out in accordance with EN 13501-1 (2018).

#### 4.2. Classification

Fire behaviour		Smoke production
$\mathrm{C}_{\mathrm{fl}}$	-	s1

Classification:  $C_{fl} - s1$ 

## 4.3. Field of application

This classification is valid for the following end use applications:

Loose laid and glued over a wood panel particle board without flame retarded classified  $C_{\rm fl}$ -s1 with a density  $\geq 510 \, {\rm kg/m^3}$  and over a fibre-cement board  $A1_{\rm fl}$  or  $A2_{\rm fl}$  with a density  $\geq 1350 \, {\rm kg/m^3}$ .

This classification is valid for the following product parameters:

• A nominal mass per unit area of: 4000 g/m<sup>2</sup>

A nominal thickness of: 5,6 mm
A nominal pile thickness of: 2,4 mm

## 5. Limitations

This classification document does not represent type approval or certification of the product.

"The classification assigned to the product in this report is appropriate to a declaration of conformity by the manufacturer within the context of system 3 of AVCP and CE marking under the Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of constructions products.

The manufacturer has made a declaration, which is held on file. This confirms that the products design requires no specific processes, procedures or stages (no addition of flame-retardants, limitation of organic content, or addition of fillers) that are aimed at enhancing the fire performance in order to obtain the classification achieved. As a consequence the manufacturer has concluded that system 3 attestation is appropriate.

The test laboratory has, therefore, played no part in sampling the product for the test, although it holds appropriate references, supplied by the manufacturer, to provide for traceability of the samples tested."

Head of Tests David VANDIERDONCK For the SARL C.R.E.T. The Technical Director Marc WELCOMME

End of the classification report