

SUBFLEX DLW MARMORETTE SPORT 3.2

PRODUCT CHARACTERISTICS				
	Standard	Requirements	Unit	Results
FULL SYSTEM DESCRIPTION				
Dimensions panels			ml x ml	1,235 x 0,46 (ep: 18,8 mm)
Dimensions absorbing foams			ml x ml	2,0 x 1,6 (ep :15 mm)
Total thickness of the system	EN ISO 24346	-	mm	37
Total weight of the system	EN ISO 23997	-	kg/m ²	21,3
TOP FLOORING DESCRIPTION "DLW Marmorette"				
Surface treatment	-	-	-	Neocare
Surface complex	-	-	-	Linoleum DLW MARMORETTE
Thickness	EN ISO 24346	-	mm	3,2
Weight	EN ISO 23997	-	kg/m ²	3,8
Length	EN ISO 24341	-	ml	28
Width	EN ISO 24341	-	cm	200
SPORT PROPERTIES				
Shock absorption	EN 14808	≥ 40	%	A3
Vertical Deformation	EN 14809	≤ 5	mm	3
Sliding Coefficient	EN 13036-4	80 à 110	-	106 - 110
Ball Bounce	EN 12235	≥ 90	%	97 - 99
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	no degradation
Rolling Load resistance	EN 1569	≤ 0,5	mm	0,3
Indentation resistance	EN 1516	≤ 0,5	mm	0,02
CLASSIFICATION				
Fire	EN 13501-1	-	-	
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1)	ISO 22196			> 99 % inhibits growth
DECLARATION OF PERFORMANCE				
		-	-	Fire Shock Absorption Sliding Coefficient Abrasion Resistance Rolling Load Resistance

(1) The implementation of an effective cleaning method is the best defence against infection