












REC 60 | 4'11" | 100% recyclable


SAFER PLAY WITH IMPROVED CUSHIONING AND DURABILITY

REC 60 offers more cushioning as well as thicker wearlayer, making it a great option for sports activities combined with some multipurpose activities

- ▶ 0.24" (6 mm) thick with 0.06" (1.5 mm) thick vinyl wearlayer
- ▶ Impact Force Reduction : $\geq 27\%$ - $\leq 33\%$
- ▶ Provides cushion and safety for children and teens from recess to sports activities
- ▶ Meets ASTM F2772 Class 2 for safe sports and play
- ▶ Wood designs are available in 86' 6" long rolls designed for standard gymnasium court sizes, which means fewer seams and better looking floors
- ▶ PURProtect® surface treatment for no-wax, easy maintenance, and enhanced stain resistance
- ▶ Noise control management up to IIC 59



SAFER PLAY WITH IMPROVED CUSHIONING AND DURABILITY

DESCRIPTION	STANDARDS	REQUIREMENTS	WOOD DESIGN	SOLID COLOR
PRODUCT DESCRIPTION				
Reference Specification	ASTM F1303	-	Type 1, Grade 1	Type 1, Grade 1
Surface Treatment	-	-	PUR Protect® UV Factory Applied	PUR Protect® UV Factory Applied
Foam	ASTM F1303	-	Class C: Cushion Foam Backing	Class C: Cushion Foam Backing
Total Thickness	ASTM F386	-	0.24" (6.0 mm)	0.24" (6.0 mm)
Roll Width	-	-	4' 11" (1.5 m)	
Roll Length	-	-	86' 6" (26.4 m)	67' 3" (20.5 m)
Weight	-	-	0.76 lb/ft² (3.7 kg/m²)	0.76 lb/ft² (3.7 kg/m²)
TECHNICAL CHARACTERISTICS				
Sport Properties	ASTM F2772	Class 1	Class 2	Class 2
Force Reduction / Cushioning	ASTM F2569	≥ 10%	≥ 27% - ≤ 33%	≥ 22% - ≤ 27%
Impact Sound (IIC)	ASTM E989 (ASTM E492)	-	IIC 59	IIC 59
Fire Rating	ASTM E648	Class 1	Class 1	Class 1
SUSTAINABILITY HEALTH & SAFETY				
Naturally Bacteriostatic: Combats MRSA, E. coli and S. aureus*	-	-	OK	OK
Allergen Free	-	-	OK	OK
Indoor Air Quality / Low Emitting Materials	EQc2 LEED v4	-	FloorScore® Certified	FloorScore® Certified
TVOC After 28 Days	ISO 16000-6	-	<100 µg/m³	<100 µg/m³
Ease of Maintenance	-	-	No Wax, No Buff for Life / PUR Protect®	No Wax, No Buff for Life / PUR Protect®
Plant Certifications	-	-	ISO 14001 and ISO 9001	ISO 14001 and ISO 9001
Restriction Use of Harmful Chemicals	Mrc4 LEED v4	-	Complies with REACH	Complies with REACH
Production Waste	-	-	100% Manufacturing Waste Recycled	100% Manufacturing Waste Recycled
Recycled Content	Mrc3 LEED v4	-	36%	36%
End of Life	-	-	100% Recyclable	
INSTALLATION METHOD				
Full-Spread Adhesive	ASTM F2170 (F1869)	≤ 95% RH (≤ 10lb)		
Moisture Mitigation System		≤ 92% RH (≤ 10 lb)	ISOLSPORT	
WARRANTY	15-year limited warranty when installed in accordance with Gerflor's installation instructions.			

*The implementation of an effective cleaning method is the best defense against infection.