

FINISHING OF CONNOR SPORTS® MODULOCK FLOORING

Connor Sports® Modulock flooring is protected with a UV-cured multilayer PU-based sports sealer. Permanent game lines can be painted and play areas can be tinted by following the recommendations below.

The products used must meet the requirements of EN 14904 (indoor surfaces for multi-sports use).

When applying the products, carefully follow the manufacturer's recommendations (cleaning the surface before application, conditions for applying the product, drying, first use, etc.).

1. PREPARING THE FLOORING

Before applying the products, the flooring must be clean and dry. Identify and mark out the areas where paint and sealers need to be applied.

Lightly sand the areas concerned with 120 grit sandpaper. Carefully remove all dust.

2. GAME LINE PAINTING

SPORT THIXO TRACES paint from Blanchon and BONA SPORTIVE PAINT from Bona are suitable for game lines.

Apply the chosen paint to the previously sanded game lines.

Refer to the datasheets and comply with the application and protection rules specified by the paint manufacturers.

3. SURFACE DIFFERENTIATION

To achieve the finish expected by the customer, we would advise you to check the finish by first applying the product to a spare panel before installation.

BONA SUPERSPORT sealer from Bona are suitable for this use.

Bona's sealer can be coloured with 5% Mix Color White for a lighter finish or 5% Mix Color Walnut for a darker wood finish.

4. APPLYING AND REMOVING STICKERS

The stickers used must be recommended by the suppliers for sealed sports flooring.

Prior to application, test on a risk-free area to check that the sticker is compatible.

When removing a sticker, there is a risk of affecting the flooring's protective finish.

You are strongly advised to use a low-temperature heat gun to loosen up the sticker's adhesive. Removing the sticker will be easier and safer.

5. RENOVATING THE FLOORING

To completely renovate the flooring, sand the entire surface down to the wood and apply the chosen products and finishes according to the manufacturer's recommendations.

