



	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
	PRODUCT DESCRIPTION			
Surface treatment	-	-	-	Protecsol [®] TRIPLE ACTION [®]
Surface complex	-	-	-	100% pur PVC
Foam	-	-	-	COMFORT CXP [®]
Thickness	EN ISO 24346	-	mm	3.7
Weight	EN ISO 23997	-	kg/m ²	1.9
Length	EN ISO 24341	-	lm	16
Width	EN ISO 24341	-	lm	1.5
	SPORT PROPERTIES			
Shock absorption	EN 14808	≥ 25	%	≥ 16
Vertical deformation	EN 14809	≤ 3.5	mm	≤ 2
Sliding coefficient	EN 13036-4	80 to 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	-
	TECHNICAL CHARACTERISTICS			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
	CLASSIFICATION			
Fire	EN 13501-1	-	-	Cfl,s1
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1)	ISO 22196	-	-	> 99 % inhibits growth
	DECLARATION OF PERFORMANCE			
	DOP-005-1022-A	-	-	Fire Sliding Coefficient Abrasion Resistance
	INSTALLATION METHODS			
	Gerflor's recommendation	Unit	Results	
Loose lay installation with double sided adhesive tapes	On existing subfloors (wooden floors, PVC floors,...)	-	-	

(1) The implementation of an effective cleaning method is the best defence against infection