

|                                                                                     |                            |             |                                                                                  |                  |
|-------------------------------------------------------------------------------------|----------------------------|-------------|----------------------------------------------------------------------------------|------------------|
|    | RECREATION LEISURE 45      |             |                                                                                  |                  |
|                                                                                     | Uni/ Wood                  |             |                                                                                  |                  |
|                                                                                     | PRODUCT CHARACTERISTICS    |             |                                                                                  |                  |
|                                                                                     | Standard                   | Requirement | Unit                                                                             | Results          |
|                                                                                     | PRODUCT DESCRIPTION        |             |                                                                                  |                  |
| Surface treatment                                                                   | -                          | -           | -                                                                                | PUR PROTECT      |
| Foam                                                                                | -                          | -           | -                                                                                | Closed cell foam |
| Thickness                                                                           | ISO 24346                  | -           | mm                                                                               | 4.5              |
| Weight                                                                              | ISO 23997                  | -           | kg/m2                                                                            | 2.8              |
| Length                                                                              | ISO 24341                  | -           | lm                                                                               | 20.5             |
| Width                                                                               | ISO 24341                  | -           | m                                                                                | 2                |
|                                                                                     | SPORT PROPERTIES           |             |                                                                                  |                  |
| Vertical deformation                                                                | EN 14809                   | ≤ 5.0       | mm                                                                               | ≤ 3.5            |
| Sliding coefficient                                                                 | EN 13036-4                 | 80 to 110   | -                                                                                | 80 to 110        |
| Ball bounce                                                                         | EN 12235                   | ≥ 90        | %                                                                                | ≥ 90             |
|                                                                                     | TECHNICAL CHARACTERISTICS  |             |                                                                                  |                  |
| Abrasion resistance                                                                 | EN ISO 5470-1              | ≤ 1000      | mg                                                                               | ≤ 350            |
| Impact resistance                                                                   | EN 1517                    | ≥ 8         | Nm                                                                               | ≥ 8              |
| Indentation resistance                                                              | EN 1516                    | ≤ 0.5       | mm                                                                               | ≤ 0.5            |
|                                                                                     | CLASSIFICATION             |             |                                                                                  |                  |
| TVOC after 28 days                                                                  | ISO 16000 - 6              | µg/m3       | < 100                                                                            | < 100            |
| Certification                                                                       | -                          | -           | -                                                                                | Floorscore®      |
| Fire resistance                                                                     | EN 13501 - 1               | -           | -                                                                                | Cfl - s1         |
| Anti-bacterial activity (1)                                                         | ISO 22196                  | -           | -                                                                                | > 99% 24H        |
| Anti-viral activity                                                                 | ISO 21702                  | -           | -                                                                                | > 99% 24H        |
|                                                                                     | DECLARATION OF PERFORMANCE |             |                                                                                  |                  |
|  | EN14904                    | -           | Fire<br>Sliding Coefficient<br>Abrasion Resistance<br>Resistance to rolling load |                  |

EN2509



Health & Safety



ISO 14001



Recycling



(1) The implementation of an effective cleaning regime is the most important defence against infections.