

| DESCRIPTION | STANDARDS | REQUIREMENTS | TARASAFE ULTRA |
|--|---|--------------|--------------------------------------|
| PRODUCT DESCRIPTION | | | |
| Reference Specification* | ASTM F1303 | - | Type 1, Grade 1 |
| Backing | ASTM F1303 | - | Class B |
| Construction | - | - | Heterogeneous Sheet Flooring |
| Surface Treatment/Maintenance | - | - | SparClean® |
| Gauge Total Thickness | ASTM F386 | > 0.075" | 0.080" (2.0 mm) |
| Roll Width | - | - | 6'6" (2.0 m) |
| Roll Length | - | - | 66' (20 m) |
| Coverage/Roll | - | - | 430.6 ft² (40 m²) |
| Weight | - | - | 0.48 lb/ft² (2360 g/m²) |
| PERFORMANCE | | | |
| Static Load Resistance & 175 psi | ASTM F970 | ≤ 0.005" | Meets Requirements |
| Abrasion | ASTM F510 | - | Meets Requirements |
| Indentation - Residual | ASTM F1914 | ≤ 0.007" | Meets Requirements |
| Flexibility | ASTM F137 | > 1.5" | Meets Requirements |
| DCOF Wet | ANSI A137.1 | ≥ 0.42 | Meets Requirements |
| Slip Resistance Wet: Ramp test with oil | DIN 51130 | - | R10 |
| Chemical & Stain Resistance | ASTM F925 | - | Meets Requirements |
| Resistance to Heat | ASTM F1514 | ΔE ≤ 8 | Meets Requirements |
| Resistance to Light | ASTM F1515 | ΔE ≤ 8 | Meets Requirements |
| Coefficient of Friction | ASTM D2047 | - | .81 leather / 1.0 neolite |
| Impact Insulation (IIC) | ASTM E989 (ASTM E492) | - | IIC 46 |
| Fire Rating (Flame Spread) | ASTM E648 | Class 1 | Meets Requirements |
| Fire Rating (Flaming & Non-Flaming) | ASTM E662 | - | Meets Requirements |
| ENVIRONMENT HEALTH & SAFETY | | | |
| Bacterio-Static** | ISO 22196 | - | Inhibits spread of infections at 99% |
| Manufacturing Plant Certifications | ISO 9001, 14001, 50001 | - | Quality, Environment, Energy |
| Environmental Product Declaration (EPD) | LEED v5 | - | Product-Specific Type III |
| Material Ingredients: Health Product Declaration (HPD) | LEED v5 | - | Self-Declared |
| No Harmful Chemicals | European Chemicals Agency (ECHA) | - | 100% REACH Compliant |
| Sourcing of Raw Material: Recycled Content | Average Pre-Consumer Content | - | 29% |
| Indoor Air Quality | California Standard 01350 | - | FloorScore® Certified |
| Production Waste | In-Plant Recycling | - | 100% Manufacturing Waste Recycled |
| TVOC after 28 days | ISO 16000-6 | - | < 100 µg/m³ |
| WARRANTY | 10-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on gerflorusa.com | | |

*Rubber leaves indelible stains on synthetic floorings: Do not use mats or any other products with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

**The best defense against the spread of infections is the implementation of an effective cleaning method.