

DESCRIPTION	STANDARDS	REQUIREMENTS	TARASAFE ULTRA H20
PRODUCT DESCRIPTION			
Reference Specification*	ASTM F1303	-	Type II, Grade 1
Backing	ASTM F1303	-	Class B
Construction	-	-	Heterogeneous Sheet Flooring
Gauge Total Thickness	ASTM F386	> 0.075"	0.080" (2.0 mm)
Roll Width	-	-	6'6" (2.0 m)
Roll Length	-	-	66' (20 m)
Coverage/Roll	-	-	430.6 ft ² (40 m ²)
Weight	-	-	0.49 lb/ft ² (2400 g/m ²)
PERFORMANCE			
Static Load Resistance & 175 psi	ASTM F970	≤ 0.005"	Meets Requirements
Indentation - Residual	ASTM F1914	≤ 0.007"	Meets Requirements
Flexibility	ASTM F137	> 1.5"	Meets Requirements
DCOF Wet	ANSI A137.1	≥ 0.42	-
Slip Resistance Wet: Ramp test with oil Barefoot only	EN 13845	-	R13+
Slip Resistance Wet: Ramp test with oil	DIN 51130	-	R11
Resistance to Heat	ASTM F1514	ΔE ≤ 8	Meets Requirements
Resistance to Light	ASTM F1515	ΔE ≤ 8	Meets Requirements
Coefficient of Friction	ASTM D2047	-	0.82 leather / 0.84 neolite
Fire Rating (Flame Spread)	ASTM E648	Class 1	Meets Requirements
Fire Rating (Flaming & Non-Flaming)	ASTM E662	-	Meets Requirements
ENVIRONMENT HEALTH & SAFETY			
Bacterio-Static**	ISO 22196	-	Inhibits spread of infections at 99%
Manufacturing Plant Certifications	ISO 9001, 14001, 50001	-	Quality, Environment, Energy
Environmental Product Declaration (EPD)	LEED v5	-	Product-Specific Type III
Material Ingredients: Health Product Declaration (HPD)	LEED v5	-	Self-Declared
No Harmful Chemicals	European Chemicals Agency (ECHA)	-	100% REACH Compliant
Sourcing of Raw Material: Recycled Content	Average Pre-Consumer Content	-	39%
Indoor Air Quality	California Standard 01350	-	FloorScore® Certified
Production Waste	In-Plant Recycling	-	100% Manufacturing Waste Recycled
TVOC after 28 days	ISO 16000-6	-	< 100 µg/m ³
WARRANTY	10-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on gerflorusa.com		

*Rubber leaves indelible stains on synthetic floorings: Do not use mats or any other products with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

**The best defense against the spread of infections is the implementation of an effective cleaning method.