

IN STOCK
NOW

Tarasafe Ultra

High performance vinyl safety flooring for heavy traffic contract applications



Compact
sheet

R10

Slip Resistant

**HSE
36+**

Slip Resistant

20

Rtm/Rz
Roughness



Heavy traffic

T

Wear group

SparClean®

Treated



Easy to cut

A sustainable choice

Also available in NEW




100% recyclable



Looselay **hop**




REACH compliant




7724 Calcium

NCS: 2002-Y / LRV: 53.3




7383 Diopside

NCS: 1005-Y20R / LRV: 59.6




8701 Opal

NCS: 1500-N / LRV: 59.1




7482 Halite

NCS: 3030-R90B / LRV: 31.8




8704 Pebble

NCS: 3000-N / LRV: 44.1




6348 Clay

NCS: 3005-Y20R / LRV: 38.7




7792 Galena

NCS: 4502-B / LRV: 28.8




2432 Larimar

NCS: 3030-B10G / LRV: 26.3




6591 Serpentine

NCS: 3010-G / LRV: 32.4




6088 Andalusite

NCS: 3020-Y40R / LRV: 35.9




8709 Granite

NCS: 5502-B / LRV: 25.4




8420 Azurite

NCS: 4030-B / LRV: 17.1




8592 Aventurine

NCS: 3030-G / LRV: 32.6




3183 Bauxite

NCS: 4010-Y50R / LRV: 28.3




8717 Obsidian

NCS: 7502-B / LRV: 10.1




9127 Meteorite

NCS: 5030-R90B / LRV: 11.7



6593 Epidote

NCS: 5020-B30G / LRV: 19.1



7307 Copper

NCS: 4040-Y80R / LRV: 18.5



Colour reference available
as Tarasafe Ultra H₂O



Colours not highlighted
with **hop** are available on
MOQ and leadtime



Scan here
for matching
WELD RODS

NCS: Natural Colour System
LRV: Light Reflectance Value

Gerflor®

Tarasafe Ultra

Tarasafe Ultra is a hardwearing safety flooring collection that comprises of a PVC wear layer and deeply inlaid mineral crystal particles (patented) and coloured chips for a decorative design. Tarasafe Ultra is available in a Compact format and selected references are now also available from stock in a Looselay **hop** format. Colours not marked with a **hop** logo are available on MOQ and lead time, contact us for details.

It is suitable for heavy traffic areas and is ideal for hardworking contract applications. It delivers Safety in Numbers, with a PTV >36+ slip resistance (Dry & Wet), a R10 wet slip resistance rating and >20 Rtm/Rz surface roughness in accordance with HSE guidelines.

The revolutionary SparClean® surface treatment improves the product performance in terms of stain resistance and durability.

Recycled content: Compact 29%, Looselay **hop** 29%.

Also available in **NEW**



Looselay **hop**

- > Adhesive free
- > Quick and easy to install
- > Easy to re-use and re-install
- > Suitable for up to 97% Relative Humidity (RH)*
- > Can be walked on immediately
- > Each roll of Tarasafe Ultra **hop** is supplied with 2x251m HOP TAPE 75 holding tape

* Installation instructions must be followed.

Tarasafe Ultra

Description			Compact	Looselay hop
Total thickness	EN ISO 24346	mm	2.0	2.0
Thickness of wearlayer	EN ISO 24340	mm	0.85	0.85
Weight	EN ISO 23997	g/m ²	2360	2460
Width/Length of sheet	EN ISO 24341	cm/ml	200/20	200/20
Classification				
Norm/Product specification	-	-	EN ISO 10582	EN ISO 10582
European classification	EN ISO 10874	class	34-43	34-43
Fire rating	EN 13501-1	class	Bfl-s1	Bfl-s1
Static electrical propensity	EN 1815	kV	≤ 2	≤ 2
Slip resistance: Pendulum Test (dry & wet)	EN 16165:2021 – Appendix C (BS 7976-2)	PTV	> 36	> 36
Surface roughness	-	µm	Rz ≥ 20	Rz ≥ 20
Slip resistance wet: Ramp test with oil	EN 16165:2021 – Appendix B (DIN 51130)	class	R10	R10
Performances				
Wear resistance	EN 660.2	mm ³	≤2	≤2
Wear Group	-	group	T	T
Type Binder content	EN ISO 10582	type	I	I
Dimensional stability	EN ISO 23999	%	≤ 0.40	≤ 0.40
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10	≤ 0.10
Residual indentation (average measure)	-	mm	≤ 0.03	≤ 0.03
Castor chair test (type W)	ISO 4918	-	OK	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	0.25
Colour fastness	EN ISO 105-B02	degree	≥ 6	≥ 6
Surface treatment	-	-	SparClean®	SparClean®
Chemical products resistance	EN ISO 26987	-	OK	OK
Anti-bacterial activity (MRSA) ⁽¹⁾	ISO 22196	-	> 99% inhibits growth	> 99% inhibits growth
Environment / indoor air quality				
TVOC after 28 days	ISO 16000-6	µg/m ³	< 100	< 100
Certification	-	-	Floorscore®	Floorscore®
CE marking				
			EN 14041	

(1) The implementation of an effective cleaning method is the best defence against infection.

Uniclass Pr_35_57_71_61			
CI / SFB			
	(43)	n6	

UK reference



Installation and Maintenance Guidelines, as well as complementary ranges available on our Gerflor website.



IMPORTANT: The information contained in this document is valid from 9/2025 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force. Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.