

DESCRIPTION 规格			
Type 类型	-		DSR02
Format 形式	-		Roll卷材
Embossing 压纹	-		Hammered锤击纹
Total thickness 总厚度	HG/T 3747.1 (ISO 24346)	mm	2.0
Width of sheet 卷宽	HG/T 3747.1 (ISO 24341)	cm	122
Length of sheet 卷长	HG/T 3747.1 (ISO 24341)	lm	15
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	HG/T 3747.1
Fire rating 防火等级	GB 8624 - 2012	class	B1
PERFORMANCES 性能			
Shore A hardness 邵氏A 硬度	GB/T 531.1 (ISO 48-4)	-	90±5
Abrasion resistance 耐磨	GB/T 9867 (ISO 4649) Method A	mm ³	≤250
Flexibility 柔韧性	HG/T 3747.1 (ISO24344 Method A)	-	OK
Residual indentation 残余凹陷度	HG/T 3747.1 (ISO 24343-1)	mm	0.20
Dimensional stability 尺寸稳定性	HG/T 3747.1 (ISO 23999)	%	≤ 0.4
Tear strength 撕裂强度	GB/T 529 (ISO 34-1)	kN/m	≥ 20
Colour fastness 色牢度	GB/T 8427	degree	≥ 3
Castor chair resistance 抗脚轮测试能力	ISO 4918	-	OK
Cigarette resistant 耐烟头	HG/T 3747.1	Rating	≥ 3
Static performance 抗静电性能	EN 1815	kV	≤2
Dry Slip resistance 抗干滑	EN 13893	-	≥ 0.30
Chemical product resistance 抗化学耐污性	HG/T 3747.1 (ISO 26987)	-	OK
ENVIRONMENT / INDOOR AIR QUALITY 环保 / 室内空气质量			
TVOC ₍₁₎ after 28 days 28天后TVOC排放量	ISO 16000 - 6	µg/m ³	< 1000
Toxic testing 有毒有害物质检测	HG/T 3747.1	-	Pass

(1) TVOC即挥发性有机化合物总排放量