

RECREATION 85

PRODUCT DESCRIPTION	Standard	Requirement	Units	RECREATION 85
Surface treatment	-	-	-	PUR PROTECT
Surface complex	-	-	-	Wear layer 100 % pure PVC
Foam	-	-	-	Closed cell foam
Thickness	EN ISO 24346	-	mm	8.5 mm 
Weight	EN ISO 23997	-	kg/m²	4,6
Length	EN ISO 24341	-	lm	20.5 Standart
Width	EN ISO 24341	-	lm	1,5

SPORT PROPERTIES

Shock absorption	EN 14808	≥ 35	%	P2  ≥35
Vertical deformation	EN 14809	≤ 3	mm	≤ 3
Sliding coefficient	EN 13036-4	80 - 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	≥ 90

TECHNICAL CHARACTERISTICS

Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Indentation resistance	EN 1516	≤ 0,5	mm	≤ 0,5

CLASSIFICATION

Fire	EN 13501-1	-	-	
Anti-bacterial activity (E. coli- S. aureus - MRSA)*	ISO 22196	-	-	> 99 % inhibits growth

	DOP-005-1007-A	-	-	Fire Sliding Coefficient Abrasion Resistance Rolling Load Resistance
---	----------------	---	---	---

* The implementation of an effective cleaning method is the best defence against infection