

DESCRIPTION

Total Thickness	EN ISO 24346 (EN 428)	mm	4.50
Thickness of the wearlayer	EN ISO 24340 (EN 429)	mm	0.55
Weight	EN ISO 23997 (EN 430)	g/m ²	7422
Format	EN ISO 24342 (EN 427)	cm	22.8 x 152.4
Tiles per carton		No / sqm	7 / 2.44

CLASSIFICATION

Product	-	-	EN 649
European Classification	EN ISO 10874 (EN 685)	class	33/42
Fire Rating	AS ISO9239-1	kW/m ² smoke%/min	9.9 171
Static Electrical Propensity	EN 1815	kV	< 2
Slip resistance	AS4586	class	R10 / P3

PERFORMANCES

Wear Group	EN 649	-	T
Dimensional Stability	EN ISO 23999	%	≤ 0,10
Residual Indentation	EN ISO 24343-1	mm	0,05
Impact sound insulation	AS ISO 717-2- 2004	LnTw	55
Colour Fastness	EN 20 105 - B02	degree	≥ 6
Surface Treatment	-	-	PU
Castor Chair resistance	ISO 4918	cycle	25000
Guarantee Residential		years	Lifetime
Guarantee Commercial		years	15

ENVIRONMENT

VOC after 28 days	ISO 16000-6	µg/ m ³	< 100
-------------------	-------------	--------------------	-------