

DESCRIPTION 规格

Total thickness 总厚度	EN ISO 24346	mm	2
Weight 重量	EN ISO 23997	g/m ²	3300
Width length of sheet 卷宽	EN ISO 24341	cm/lm	200/20

CLASSIFICATION 类别

Norm / Product specification 产品规范	-	-	EN ISO 10581
Fire rating 防火等级	IMO认证	-	MSC 307(88) Part 5
			MSC 307(88) Part 2
	海事认证	-	MED
			US Coast Guard
			Transport Canada
SOLAS 74			
Static electrical propensity 抗静电性	EN 1815	KV	≤2

PERFORMANCE 性能

Wet slip resistance 防湿滑性	DIN EN 16165 Annex B	class	R9
Type binder content 粘合物分级	EN ISO 10581	type	II
Abrasion resistance 耐磨性	EN 660-2	mm ³	≤7.5
Abrasion group 耐磨等级	EN 649	group	M
Dimensional stability 尺寸稳定性	EN ISO 23999	%	≤ 0.4
Residual indentation 残余凹陷性	EN ISO 24343-1	mm	≤ 0.1
Thermal conductivity 热传导性	EN ISO 10456	W/(m.K)	0.25
Colour fastness 颜色稳定性	EN ISO 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	EN ISO 26987	-	OK
Anti-bacterial and fungicidal 抗菌防霉性能	-	-	OK
Special treatment 特殊维护处理	-	-	EASYCARE
TVOC after 28 days 28天后TVOC*排放量	ISO 16000 - 6	µg/m ³	<10



ClassNK

