



DESCRIPTION			
Total Thickness	EN ISO24346 (EN 428)	mm	2
Weight	EN ISO 23997 (EN 430)	g/m <sup>2</sup>	2000
Width	EN ISO 24341 (EN 426)	cm	100
Length	EN ISO 24341 (EN 426)	m	7.5
Packaging content		m <sup>2</sup>	7.5
Packaging Weight		kg	15
Article code			16980001
CLASSIFICATION			
Fire rating	EN 13501-1	class	Cfl-s1 (underlayer alone) Bfl-s1 (with Creation 55 / Creation 40 / Creation 30 / Virtuo 55 / Virtuo 30)
PERFORMANCE			
Impact sound insulation	EN ISO 717-2	dB	16
Thermal resistance	EN 12664	m <sup>2</sup> K/W	0.01
Compressive Strength	EN ISO 3386 / EN826	kPa	> 450
Compressive Strength	EN ISO 3386 / EN826	t/m <sup>2</sup>	> 45
Punctual Conformability	CEN/TS 16354	mm	~ 0.79
 			

This product is recommended by Gerflor for the following products:

- CREATION 55
- CREATION 40
- CREATION 30
- VIRTUO 55 (For class 22 use only)
- VIRTUO 30 (For class 22 use only)