


DESCRIPTION			DESIGN
Total Thickness	EN ISO24346	mm	2.00
Thickness of the wearlayer	EN ISO24340	mm	0.40
Weight	EN ISO 23997	g/sqm	3430
Size Number of tiles/planks and sqm per box	EN ISO 24342 -	mm -	184,15x1219,2 x21 / 4,71 sqm 230x1500 x13 / 4,49 sqm 457,2x914,4 x11 / 4,6 sqm
CLASSIFICATION			
Norm/Product specification	-	-	EN ISO 10582
European classification	EN ISO 10874	class	23 – 32
Fire rating	EN 13 501-1	class	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet	DIN 51130	class	R10
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group		-	T
Type binder content	EN ISO 10582	type	I
Room impact	NF S 30174	dB	77
Impact sound insulation	EN ISO 717-2	dB	4
Dimensional stability (norm)	EN ISO 23999	%	≤ 0.25
Dimensional stability (average measure value)	-	%	≈ 0.10
Residual indentation	EN ISO 24343-1	mm	≤ 0.10
Castor chair test	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Color fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	ProtecShield™
Chemical product resistance	EN ISO 26987	-	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
CE MARKING			
CE	EN 14041	-	
		-	