

DESCRIPTION			ARTE	DESIGN
Total Thickness	EN ISO24346	mm	2.50	
Thickness of the wearlayer	EN ISO24340	mm	0.70	
Weight	EN ISO 23997	g/m ²	3960	4100
Size Number of tiles/planks and sqm per box	EN ISO 24342 -	mm -	184,15x1219,2 x15 / 3,37 sqm	230x1500 x9 / 3,11 sqm
			496,5x996,5 x8 / 3,96 sqm	457,2x914,4 9 / 3,76 sqm
				609,6x609,6 9 / 3,35 sqm
				914,4x914,4 5 / 4,18 sqm
CLASSIFICATION				
Norm/Product specification	-	-	EN ISO 10582	
European classification	EN ISO 10874	Class	34 – 43	
Fire rating	EN 13 501-1	Class	Bfl-s1	
Static electrical propensity	EN 1815	kV	< 2	
Slip resistance wet	DIN 51130	classe	R10	
PERFORMANCES				
Wear resistance	EN 660.2	mm ³	≤ 2.0	
Wear group		-	T	
Type binder content	EN ISO 10582	type	I	
Room impact	NF S 30174	dB	77	
Impact sound insulation	EN ISO 717-2	dB	4	
Dimensional stability (norm)	EN ISO 23999	%	≤ 0.25	
Dimensional stability (average measure value)	-	%	≈ 0.10	
Residual indentation	EN ISO 24343-1	mm	≤ 0.10	
Castor chair test	ISO 4918	-	OK	
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	
Color fastness	EN 20 105 - B02	Degree	≥ 6	
Surface treatment	-	-	ProtecShield™	
Chemical product resistance	EN ISO 26987	-	OK	
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10	
CE MARKING				
	EN 14041	-		
		-		