

DESCRIPTION	STANDARDS	REQUIREMENTS	CREATION WELLPOINT	
PRODUCT DESCRIPTION				
Reference Specification*	ASTM F1700	-	Class III Type B	
Construction	-	-	Luxury Vinyl Tile	
Surface Treatment/Maintenance	-	-	PUR+ Matte	
Gauge Total Thickness	ASTM F386	-	0.1" (2.5 mm)	
Wearlayer Thickness	ASTM F410	-	20 mil (0.5 mm)	
Backing	ASTM F1303	-	100% Recycled Material	
Plank & Tile Sizes	-	-	7.1" x 47.25"	12" x 24"
Pieces per Box	-	-	15	18
Sq Ft per Box	-	-	34.95 ft ²	36 ft ²
PERFORMANCE				
Static Load Resistance	ASTM F970	≤ 0.005"	Meets Requirements	
Dimensional Stability	ASTM F2199	< 0.02"	Meets Requirements	
Dimensional Squareness	ASTM F2055	-	Meets Requirements	
Indentation - Residual	ASTM F1914	≤ -8%	Meets Requirements	
Flexibility	ASTM F137	> 1"	Meets Requirements	
Chemical & Stain Resistance	ASTM F925	-	Meets Requirements	
Resistance to Heat	ASTM F1514	-	Meets Requirements	
Resistance to Light	ASTM F1515	-	Meets Requirements	
Coefficient of Friction	ASTM D2047	-	Meets Requirements	
Impact Insulation (IIC)	ASTM E989 (ASTM E492)	-	IIC 39	
Fire Rating - Flame Spread	ASTM E648	Class 1	Meets Requirements	
Smoke Density (Flaming and Non-Flaming)	ASTM E662	-	Meets Requirements	
ENVIRONMENT HEALTH & SAFETY				
Bacterio-Static**	ISO 22196	-	Inhibits spread of infections at 99%	
Viro-Static**	ISO 21702	-	Inhibits growth of virus of 99.7% after 2 hours	
Manufacturing Plant Certifications	ISO 9001	-	Quality	
Environmental Product Declaration (EPD)	LEED v4 M+R	-	Product-Specific Type III	
Material Ingredients: Health Product Declaration (HPD)	LEED v4 M+R	-	Self-Declared	
Material Ingredients: REACH Optimization	European Chemicals Agency (ECHA)	-	100% REACH Compliant	
Sourcing of Raw Material: Recycled Content	Average Pre-Consumer Content	-	30%	
Indoor Air Quality / Low Emitting Materials	California Standard 01350	-	FloorScore® Certified	
Production Waste	In-Plant Recycling	-	100% Manufacturing Waste Recycled	
TVOC after 28 days	ISO 16000-6	-	<10µg/m ³	
WARRANTY	20-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on gerflorusa.com			

*Rubber leaves indelible stains on synthetic floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

** The best defense against the spread of infections is the implementation of an effective cleaning method.