



Technical Datasheet Gerfix NDT Primer

PRODUCT DESCRIPTION

Ready-to-use, low-VOC, single coat application, water-based primer designed for use with Gerfix NDT Tape.

FEATURES AND BENEFITS

- Up to 98% RH / 15 MVER / pH12
- Ready-to-use
- No need to dilute
- Fast drying formula

Technical Data	
Packaging	1 gallon (sealed bladder housed within a carton)
Weight	8.9 lbs
Color (wet)	light blue
Color (dry)	transparent
Coverage	up to 600 sq ft
VOC	< 10 g/L
Drying time	1 hour*
Minimum application temperature	65°F (18°C) and 65% RH (substrate level)
Frost resistance for 5 cycles	28°F (-2°C)
Shelf Life	12 months

*Surface profile, porosity, application depth, temp and humidity will affect dry time and coverage.

CRITICAL INSTALLATION POINTS

- For use on concrete.
- Optimum conditions for product installation are 65-85°F (18-29°C) and relative humidity below 65%.
- Thoroughly shake container.
- Do not dilute.
- Pour required amount of primer into a clean bucket.
- Allow the primer to dry for a minimum of 1 hour before applying the Gerfix NDT Tape.
- Visit gerflorusa.com for complete application instructions.

STORAGE

Store indoors in dry conditions between 55-85°F (18-28°C).

DISPOSAL

Dispose of contents and container per local, regional, and federal regulations.



Technical Datasheet Gerfix NDT Primer

IMPORTANT NOTES

- After opening, ensure the package is securely resealed. Any remaining material should be used before the end of its shelf life, provided it is stored at 55-85°F (18-28°C).
- Single coat application.
- Do not apply to wet surfaces.
- **Do not install** if the concrete surface temperature is within 5°F of dew point.
- Use patching or self-leveling compounds rated equivalent to or greater than 98% RH.

CLEAN UP

Clean tools with water immediately after use.

SAFETY GUIDELINES

Consult and follow all Safety Data Sheet (SDS) instructions available at www.GerflorUSA.com.

WARRANTY

Gerflor warrants that this product has been manufactured from the highest quality raw materials, under conditions to meet rigid quality standards established by Gerflor. Therefore, the following is made in lieu of all other warranties expressed or implied. Sellers and manufacturers' sole obligation shall be to replace such quantity of the product proven to be defective. Neither seller nor manufacturer shall be liable for any loss or damage direct or consequential arising out of the use of or the inability to use this product. Before using, user shall determine the suitability of the product for his intended use. User assumes all risks and liability whatsoever in connection therewith. No person has authority to change these terms and there are no warranties, except as herein stated.

For additional information, please contact Gerflor Customer Support at 1-877-437-3567.

Please refer to GerflorUSA.com for the latest installation instructions.

Gerflor USA, Inc.
750 Veterans Parkway
Bolingbrook, IL 60440
877-GER-FLOR (877-437-3567)
GerflorUSA.com