

# griptex

A warm and comfortable slip resistant vinyl flooring that is specifically designed for housing & renovation



This swatch book includes the selected references chosen for Epic Housing Association for Bathrooms. The range included is Gerflor Griptex.



Warm and comfortable underfoot



Sound insulating for a quieter home



Waterproof for extra hygiene



Easy to clean pureclean PU surface that doesn't trap dirt



Low potential for slip



Durable 0.35mm wearlayer that keeps the floor looking great

# Gerflor®

# Griptex

Griptex is a tough vinyl flooring with a unique patented textile backing system that offers outstanding warmth and comfort underfoot. Griptex is safer, quieter and hygienic with an easy to clean surface. Available in a range of stunning modern designs and colourways that can be used in any room in your home.

## TECHNICAL INFORMATION

Thickness	EN ISO 24346	mm	2.90
Wear layer thickness	EN ISO 24340	mm	0.35
Weight	EN ISO 23997	g/m <sup>2</sup>	2000
Width of sheet	EN ISO 24341	m	2 / 3 / 4
Length of sheet	EN ISO 24341	ml	≈ 25
Backing	-	-	Polyester (GFT)
European classification	EN ISO 10874	class	23 - 31
Impact sound insulation	EN ISO 717-2	dB	16
Fire rating	EN 13 501-1	class	Cfl-s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet: ramp test with oil	DIN 51130	class	R10
Wear group	-	group	T
Dimensional stability (requirement)	EN ISO 23999	%	≤ 0.40
Dimensional stability (average measured value)	-	%	0.05
Residual indentation (requirement)	EN ISO 24343-2	mm	≤ 0.35
Residual indentation (average value measured)	-	mm	0.20
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	pureclean GripX
Chemical products resistance	EN ISO 26987	class	OK
TVOC after 28 days	ISO 16000-6	μ/m <sup>3</sup>	< 100
Certification	-	-	Floorscore®



EN 14 041



GFT is a patented backing system from Gerflor, made from up to 95% recycled plastic bottles. It has many benefits including more warmth and comfort underfoot, sound deadening qualities and it can be laid over most existing floors by evening out small imperfections in the sub-floor - Unroll... it's done!

**For more information or to order samples please contact:**

UNITED KINGDOM  
 ☎ +44 (0) 1625 428 922  
 @ contractuk@gerflor.com  
 🌐 www.gerflor.co.uk

REPUBLIC OF IRELAND  
 ☎ +353 (0) 42 966 1431  
 @ gerflorirl@gerflor.com  
 🌐 www.gerflor.ie



1284 Verone Light Grey

## Griptex



2256 Opera Medium



2266 Empire Grey



1284 Verone Light Grey